

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Pawnee		SE ¼ SE ¼ NW ¼		5		T 22 S		R 16 E/W	
Distance and direction from nearest town or city street address of well if located within city?									
½ mile south of Larned, Ks.									
2 WATER WELL OWNER: Dale Otte									
RR#, St. Address, Box # : Rt 3						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Larned, Ks. 67550						Application Number:			
3 LOCATE WELL'S LOCATION WITH		4 DEPTH OF COMPLETED WELL: 28 ft. ELEVATION:							
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 12-14-00							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield NA gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 9.7/8 in. to 28 ft., and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well live stock							
Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yrs sample was submitted									
Water Well Disinfected? Yes No X									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) CASING JOINTS: Glued. X. Clamped.									
2 PVC 4 ABS 7 Fiberglass Threaded.									
Blank casing diameter 5 in. to 18 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 24 in., weight SDR-26 lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify) ft.									
SCREEN-PERFORATED INTERVALS: From 18 ft. to 28 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 28 ft. to 15 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug									
Grout Intervals: From 15 ft. to 0 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage barn									
Direction from well? south How many feet? 60'									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 3 Top soil									
3 13 Brown clay									
13 18 Sand & gravel									
18 20 Blue & gray clay									
20 27 Sand & gravel									
27 28 Fire clay									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-14-00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 134 This Water Well Record was completed on (mo/day/yr) 12-20-00 under the business name of Rosencrantz-Bemis by (signature) Freda Hanson									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.									