


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Pawnee		S/2-NW NW 1/4 NE 1/4	5	T 22 S	R 16 EW
Distance and direction from nearest town or city street address of well if located within city? 444 S.W. Trail St., Larned, Ks.					
2 WATER WELL OWNER: Eldon Berglund					
RR#, St. Address, Box #: 444 S. W. Trail					
City, State, ZIP Code: Larned, Ks					
Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 24.5 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 1.7 ft. 2. 0 ft. 3. 0 ft.			
		WELL'S STATIC WATER LEVEL 16.6 ft. below land surface measured on mo/day/yr 3-6-91			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 7.5/8 in. to 2.4.5 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing diameter 2 in. to 14.5 ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface 2.4 in., weight lbs./ft. Wall thickness or gauge No. S.ch. 4.0					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 24.5 ft. to 14.5 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 24.5 ft. to 12.5 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 12.5 ft. to 10.5 ft. (Bent) From 10.5 ft. to 0 (cement) From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	Abdn. underground
Direction from well? NE					
How many feet? 50 fuel storage site					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top soil			
1	4	Silt-tan			MW# 1
4	7	Clay-silty, brown, fine sand, small ls. frags.			
7	8	Silt-brown, small ls. frags.			
8	9	Silt-tan, sandy			
9	14	Sand-fine to coarse			
14	17	Clay-gray			
17	18	Sand-fine to coarse			
18	21	Sand-med to coarse, gray clay streaks			
21	24.5	Sand-coarse			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-8-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 4-8-91 under the business name of GeoCore Services, Inc. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					