

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Pawnee		1/4 S 1/2 1/4 SE 1/4		9		T 22 S		R 16 E/W	
Distance and direction from nearest town or city street address of well if located within city? 2 south, 3/4 east of Larned, Ks.									
2 WATER WELL OWNER:		Pawnee County Solid Waste RR#, St. Address, Box # : 915 Bdwy. Courthouse City, State, ZIP Code : Larned, Ks. 67550							
		Board of Agriculture, Division of Water Resources Application Number: 0123							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 36 ft. below land surface measured on mo/day/yr 5-9-94							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield na gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 10 in. to 60 ft. and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No x If yes, mo/day/yr sample was submitted							
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? Yes hth No							
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued x Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
Blank casing diameter 5 in. to 30 ft. Dia 5 in. to 50 to 60 ft. Dia in. to ft.									
Casing height above land surface 12 in., weight 258 lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 United holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 30 ft. to 50 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 20 ft. to 60 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug									
Grout Intervals: From 3 ft. to 20 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage none									
Direction from well?		How many feet?							
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0	2	Top soil							
2	9	Fine sand							
9	26	Brown clay and fine sand							
26	38	Sand and gravel							
38	41	Brown clay							
41	52	Sand and gravel							
52	55	Brown clay							
55	60	White, gray, yellow clay							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-18-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 5-27-94 under the business name of Rosencrantz-Bemis by (signature) Freda Roden									