1		ED 14/E11	1 =	WELL RECORD F	Contraction	NOM 024		mbor	Panao N	umbor
	Paw Ne		Fraction 4	NW/ WF	. Sect	ion Number	Township Nu	mber . S	Range N	_
County: Distance a	nd direction f	from nearest tow	n or city street ad	dress of well if located		10	,	<i>.</i>	, , ,	~~~
<u> </u>	Miles			on highw		•				
WATER			ton Buster	7	/					
4	ddress, Box	/11-/4					Board of A	griculture, [Division of Wate	r Resources
City, State,	ZIP Code		ed KS	67550			Application	Number:	020713	?
LOCATE	WELL'S LO	CATION WITH	4 DEPTH OF CO	MPLETED WELL						
<u> </u>	- NW	XI NE	WELL'S STATIC V Pump Est. Yield	WATER LEVEL 15 test data: Well water gpm: Well water er in. to	.5. ft. be was was	elow land surf ft. af ft. af	face measured on Iter	mo/day/yr hours pur hours pur		gpm
<u> </u>	- sw	 		Vas 3 Feedfot 6	Public water Oil field water	er supply	8 Air conditioning 9 Dewatering	12	Injection well Other (Specify	•
Ιľ	- 311 1	;	2 Irrigation		_	•	10 Monitoring well			
Į L	<u> </u>		Was a chemical/bamitted	acteriological sample su	bmitted to De		esNo ter Well Disinfecte		mo/day/yr sam No	ple was sub-
TYPE-C	BLANK C	ASING USED:		5 Wrought iron	8 Concre	te tile	CASING JOI	NTS: Glued	i Clam	oed
1 Ste	el	3 RMP (SF	₹)	6 Asbestos-Cement	9 Other (specify below	v)	Weld	ed	
2 PV	C	4 ABS		7 Fiberglass					aded	
		<i>[.6</i>	~ ~ / / / .	ft., Dia						
Casing hei	ght above la	nd surface	3 44 Delas	in., weight		ibs./f	ft. Wall thickness of	or gauge N	o	
TYPE OF	SCREEN OF	R PERFORATION	N MATERIAL:		7 PV0			estos-ceme		
1 Ste	el	3 Stainless	steel	5 Fiberglass	8 RM	P (SR)	11 Oth	er (specify)	<i>NR</i>	
2 Bra	ISS	4 Galvaniz	ed steel	6 Concrete tile	9 ABS	3		e used (op		
SCREEN (OR PERFOR	ATION OPENIN	GS ARE:	5 Gauzeo	wrapped		8 Saw cut		11 None (ope	en hole)
1 Co	ntinuous slot	3 M	ill slot	6 Wire wrapped			9 Drilled holes		. 41	
2 Lo	uvered shutte	er 4 Ke	ey punched	7 Torch o			10 Other (specify)	<i>N.</i> A	
SCREEN-F	PERFORATE	D INTERVALS:	From	ft. to	N.P	ft., Fror	m	ft. t	0	
c	DAVEL DAC	CK INTERVALS:		ft. to						
	INAVEL FAC	OR INTERVALS.	From	ft. to		ft., Fror		2		ft.
GROUT	MATERIAL	: 1. Neat o		Cement grout	3 Bentor	nite 4	Other			
Grout Inter			~	ft., From	ft. 1	to	ft., From	. .	ft. to	
		urce of possible					tock pens		bandoned water	
1 Se	ptic tank	4 Later	al lines	7 Pit privy		11 Fuel:	storage	15 O	il well/Gas well	
	2 Sewer lines 5 Cess pool			• •			ertilizer storage 16 Other (specify below)			
		er lines 6 Seep		9 Feedyard			ticide storage			
Direction f	-	West				How mai	ny feet? 100	10'		
FROM	TO		LITHOLOGIC L	.OG,	FROM	то			NTERVALS	
38	16,17	Sand +	Grave!	(43.3 aft)				,,		
16	301	Topsoil	fine sand)	(197 cuft)			This we	ll wa	s drifter	
6	3 28	CEMENT	groute	(5,91 wft)			in aprox	1973	and &	es
		•	٧				never p	UMPE	d due	to
							The low	Wat	y yield	
				100						
7 CONT	LI		D'S CEDTIEICATI	ON: This water well wa	s (1) constru	nted (2) reco	netructed or (2)	duaged use	der my juriedist	ion and was
T CONU	1AUTUH'S (MAA	1 9 1991				ord is true to the be			
			h.9,1994.	This Water We				M woh	10 , 94	unui. Nalisas
		s License No.		Inis water We	iii necora wa			17	in the	
	business nar					by (signa		- y.~	ung_	
INSTRU of Healt	CTIONS: Use type the second terms of the secon	pewriter or ball point ent, Bureau of Water,	pen. PLEASE PRESS FI. Topeka, Kansas 66620	RMLY and PRINT clearly. Plea -0001. Telephone: 913-296-55	se fill in blanks, to	underline or circle	e the correct answers. S WNER and retain one for	erd top three or your records	copies to Kansas (Department