WALL	CK WE	LL RECORD	Form WW	C-5	Division of Water Resources App. No.
1 LO	CATION	OF WATER WELL:	Fraction		Section Number Township No. Range Number
Cot	inty: Pa	wnee	1/4 NW 1/4 NE 1/	4 NE 1/4	13 T 22 S R 16 □E 🛂 W
Stre	Street/Rural Address of Well Location; if unknown, distance & direction			lirection	Global Positioning System (GPS) information:
	from nearest town or intersection: If at owner's address, check here .				Latitude: (in decimal degrees)
		1/4 East of Larned	· · · · · · · · · · · · · · · · · · ·		Longitude: (in decimal degrees)
2.5	outri, 3	1/4 East of Lamed			Elevation: (in decimal degrees)
					Datum: WGS 84, NAD 83, NAD 27
2 W	ATER W	ELL OWNER: William	Fairchild		Collection Method:
RR	#, Street	Address, Box #: 723 K R			GPS unit (Make/Model:)
		710 0 1	Ks. 67550	-	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
	, ,	Larrieu,	NS. 07000		Est. Accuracy:
3 LOC	CATE WI	ELL			
WIT	TH AN "X	" IN 4 DEPTH OF C	COMPLETED WELL.	90	ft.
SEC	CTION BO				ft. (2) ft. (3) ft.
	N	WELL'S STATI	CWATER LEVEL 43	ft h	below land surface measured on mo/day/yr. 9-21-11
	T				ft. after hours pumping gpm
	i	Dom viter to M/			
W -NW - NE - E Bore Hole Diameter 10					
W		E Bore Hole Diame			r supply Geothermal Injection well
	1	TT Damestia			
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well					
	~				Department? 🗌 Yes 🗹 No
1	S 1 mile		lay/yr sample was submi		
Water well disinfected? ✓ Yes □ No					
5 TYPE OF CASING USED: Steel V PVC Other					
CASING JOINTS: Glued Clamped Welded Threaded					
Casing diameter .5 in. to .90 ft., Diameter ft., Diameter ft.					
Casing height above land surface. 18 in., Weight SDR-26 lbs./ft., Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
Steel Stainless Steel PVC Other (Specify)					
Brass Galvanized Steel None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From 90 ft. to 70 ft., From ft. to ft.					
From ft to ft From ft to ft					
GRAVEL PACK INTERVALS: From					
GRAVEL PACK INTERVALS: From 90 ft. to 68 ft., From ft. to ft. From 63 ft. to 20 ft., From ft. to ft.					
6 GROUT MATERIAL: Neat cement Cement grout V Bentonite Other					
Grout Intervals: From 68 ft. to 63 ft., From 20 ft. to 0 ft., From ft. to					
What is	the near	est source of possible contain	nination:		
	Septic ta	nk 🔲 Lateral line	s 🗌 Pit privy 🔲 🗎	Livestock pen	ns Insecticide storage
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well					
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Well pit					
					om well 25ft.
FROM	TO	LITHOLOGI	C LOG F	FROM T	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0	32	Clay			
32	61	Sand & gravel- med			
61	70	Tan clay			
70	90	Sand & gravel- med			
		,			
		The state of the s			

	†				
	 				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged					
under my invisdiction and was a smalleted as (exclusive selection). This water well was of constructed, or plugged					
under my jurisdiction and was completed on (mo/day/year) 9-21-11 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134					
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 9-30-11					
under the business name ofRosencrantz-Bemis by (signature)					
(white, blue, process of the surface					
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					
http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212 Check: ☑ White Copy, ☐ Blue Copy, ☐ Pink Copy					