


CRAWFORD		WATER WELL RECORD		Form WWC-5		KSA 82a-1212			
1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: PAWNEE		SE 1/4 NE 1/4 SE 1/4		29		T 22 S		R 16 E 60	
Distance and direction from nearest town or city street address of well if located within city?									
LARNED 45 4E 1/2 N WESTSIDE.									
2 WATER WELL OWNER:		J.W. DRILLING CO. INC.		E CRAWFORD, LARNED, KS					
RR#, St. Address, Box #		800 E. FIRST SUITE 500		Board of Agriculture, Division of Water Resources					
City, State, ZIP Code		WICHITA, KS 67202		Application Number: T84-22					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. 35 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 1-9-84							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 7 1/8 in. to 6.0 ft. and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well							
		Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded							
2 PVC 4 ABS		7 Fiberglass Threaded							
Blank casing diameter 5 in. to 40 ft. Dia		in. to ft. Dia							
Casing height above land surface 12 in. weight 2.65 lbs./ft. Wall thickness or gauge No. 214									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: 48		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS:		From 40 ft. to 60 ft. From ft. to ft.							
GRAVEL PACK INTERVALS:		From 20 ft. to 60 ft. From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination: NONE		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well?		How many feet?							
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG				
0	6	SOIL							
6	13	CLAY							
13	20	SAND							
20	25	SANDY CLAY							
35	45	GRAVEL							
45	48	CLAY							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-9-84 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 1-16-84									
under the business name of REISER WATER WELLS & SERVICE INC. (by signature) [Signature]									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									

OFFICE USE ONLY

T

R

16

EWM

SEC.

24

SE 1/4 NE 1/4 SE 1/4