

1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number		Range Number	
County: Pawnee		NE 1/4 NW 1/4 SW 1/4	4		T 22 S		R 18 E/W	
Distance and direction from nearest town or city street address of well if located within city? 1 1/4 south of Sanford, Ks.								
2 WATER WELL OWNER:		Dan Fox			Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		809 Carnish Drive			Application Number: PN 057			
City, State, ZIP Code :		San Diego, Ca. 92107						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 142 ft. ELEVATION:						
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 32 ft. below land surface measured on mo/day/yr 7-30-97 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 1200 gpm Well water was 50 ft. after 2 hours pumping 1200 gpm Bore Hole Diameter 28 in. to 142 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X						
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped						
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded						
2 PVC 4 ABS		7 Fiberglass Threaded						
Blank casing diameter 16 in. to 82 ft. Dia in. to ft. Dia in. to ft.		Casing height above land surface 12 in. weight SDR 32.5 lbs./ft. Wall thickness or gauge No.						
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS:		From 82 ft. to 142 ft. From ft. to ft.						
GRAVEL PACK INTERVALS:		From 142 ft. to 20 ft. From ft. to ft.						
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.		What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)		13 Insecticide storage none						
Direction from well?		How many feet?						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS			
0	3	Top soil						
3	30	Dark brown clay						
30	40	Fine sand						
40	44	Sandy clay						
44	45	Sand and gravel						
45	55	Dark clay						
55	80	Sand streaks of clay						
80	110	Sand clean						
110	122	Sandy brown clay						
122	142	Sand and gravel						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-1-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 8-5-97 under the business name of Rosencrantz-Bemis by (signature) Fredia Jackson								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								