


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Pawnee	SW 1/4 SW 1/4 SE 1/4	6	T 22 S	R 18 E

Distance and direction from nearest town or city street address of well if located within city?

Approx. 1 1/4 mi. south and 1 1/2 mi. west of Sanford, KS

2 WATER WELL OWNER:	Marvin Finger	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Route 1 - Box 14	Application Number: not available
City, State, ZIP Code :	Rozel, KS 67574	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 156 ft. ELEVATION: unknown
	Depth(s) Groundwater Encountered 1. 49 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 49 ft. below land surface measured on mo/day/yr 6/27/85
	Pump test data: Well water was 86 ft. after 1 hours pumping 1300 gpm
	Est. Yield 1100 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 30 in. to 156 ft. and in. to ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR) Transite	6 Asbestos-Cement	Connecting X Welded
2 PVC	4 ABS	7 Fiberglass	Bands Threaded
Blank casing diameter 16 in. to 91 ft. Dia			
Casing height above land surface 12 in. weight 34 lbs./ft. Wall thickness or gauge No. 3/4"			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
11 Other (specify)			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) 125 Double Slot
SCREEN-PERFORATED INTERVALS:	From 91 ft. to 156 ft.		
	From ft. to ft.		
GRAVEL PACK INTERVALS:	From 10 ft. to 156 ft.		
	From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0 ft. to 10 ft.			
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	Field
Direction from well? all			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	40	Topsoil & tan clay			
40	69	Sand & gravel, fine to very fine			
69	86	Brown & gray clay			
86	105	Sand & gravel, fine to very fine			
		some med. w/a few thin clay streaks			
105	116	Tan & gray clay			
116	127	Sand & gravel, fine to very fine, clean			
127	142	Soft brown & gray clay			
142	153	Dakota formation w/med. to fine sand & gravel, clean w/coarse rocks			
153	156	Gray & red Dakota clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/27/85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185. This Water Well Record was completed on (mo/day/yr) 7/22/85 under the business name of Clarke Well & Eq., Inc. by (signature)
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.