


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Pawnee</u>		NW 1/4 NW 1/4 SW 1/4	5	T 22 S	R 18 E/W
Distance and direction from nearest town or city street address of well if located within city? <u>1 south 1/2 west of Sanford</u>					
2 WATER WELL OWNER: <u>Mrs. Frank Brownlee</u> <u>Texas Energies</u> RR#, St. Address, Box #: <u>Larned, Ks.</u> <u>Box 947</u> City, State, ZIP Code: <u>Pratt, Ks. 67124</u> Board of Agriculture, Division of Water Resources Application Number: <u>T83-706</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>105</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>16</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ... <u>33</u> ft. below land surface measured on mo/day/yr ... <u>12-22-83</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield ... <u>NA</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter ... <u>10</u> in. to ... <u>105</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>HTH</u> No			
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>x</u> Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter ... <u>5</u> in. to ... <u>85</u> ft., Dia in. to ft., Dia in. to ft. Casing height above land surface ... <u>18</u> in., weight lbs./ft. Wall thickness or gauge No. <u>258</u> TYPE OF SCREEN OR PERFORATION MATERIAL: <u>7 PVC</u> 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped <u>8 Saw cut</u> 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From ... <u>8.5</u> ft. to ... <u>105</u> ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From ... <u>1.0</u> ft. to ... <u>105</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 <u>Cement grout</u> 3 Bentonite 4 Other Grout Intervals: From ... <u>0</u> ft. to ... <u>10</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? <u>west</u> How many feet? <u>80</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	16	Clay			
16	19	Gravel			
19	42	Clay			
42	98	Sand and gravel			
98	105	Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) ... <u>12-22-83</u> ... and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. ... <u>134</u> ... This Water Well Record was completed on (mo/day/yr) ... <u>12-30-83</u> ... under the business name of <u>Rosencrantz-Bemis Ent.</u> by (signature) <u>Lora Dodson</u> INSTRUCTIONS: Use typewriter or ball point pen, <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

SEC.

NW 1/4 NW 1/4 SW 1/4