VATE	R WEI	LL RECORD	Form W	WC-5	Division of Wate	r Resources App. N	29065
	LOCATION OF WATER WELL:		Fraction 1/4 SE 1/4 SW 1/4 NW 1/4		Section Number	Township No.	Range Number
	County: Pawnee				8	T 22 S	R 18 □E 🗸 W
		Address of Well Location;			Global Positioning System (GPS) information:		
	from nearest town or intersection: If at owner's address, check here				Latitude: (in decimal degrees) Longitude: (in decimal degrees)		
1 1/2 South, 1/4 West of Sanford					Elevation: (In decimal degrees)		
					Datum: WGS 84, NAD 83, NAD 27		
WATER WELL OWNER: Neil Meckfessel RR#, Street Address, Box #: 1150, 240th, Ave					Collection Method:		
	Ch. Co. A. 7TD Co. La				☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
. City	, State, 2	Rozel, F	KS 67574	Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m			
3 LOCATE WELL							
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 181 ft.						
SEC	SECTION BOX: Depth(s) Groundwater Encountered (1)						(3) In.
	Pump test data: Well water was 95						ning 750 gnm
3.13	EST. YIELD, 853gpm. Well water was. 106						
W	E Bore Hole Diameter 30in. to181						
A	WELL WATER TO BE USED AS: Public water supply Geothermal Injection						
SV	SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify belo						
	☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well						
	S If yes, mo/day/yr sample was submitted						
mile Water well disinfected? ☑ Yes ☐ No							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: V Glued Clamped Welded Threaded							
Casing diameter 16. in. to .181 ft., Diameter in. to ft., Diameter in. to ft.							
Casing height above land surface18							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)							
SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
□ Louvered shutter □ Key punched □ Wire wrapped ☑ Saw cut □ Other (specify) SCREEN-PERFORATED INTERVALS: From 181 ft. to 81 ft., From ft. to ft.							
Fromft. toft. Fromft to							
GRAVEL PACK INTERVALS: From 181 ft. to 20 ft., From ft. to ft. to							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other							
Grout Intervals: From							
Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)							
	Sewer lines Cesspool Sewage lagoon Fuel				age Abandoned water well		
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well None Direction from well							
FROM	TO	LITHOLOG		FROM			JGGING INTERVALS
0	35	Top soil & clay	10 100	1 1(0141	LITTO, LC	o (cont.) or FLC	COMO INTERVALS
35	50	Sand		 			
50	77	Clay					
77	97	Sand & gravel					
97	114	Sand & gravel & clay					
114	181	Sand					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged							
ander my jurisdiction and was completed on (mo/day/year) .4-16-15 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 5-15-15							
under the business name of Rosencrantz- Bemis Ent Inc. INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send one copy to							
	Kansas De	partment of Health and Environr	nent, Bureau of Water, Geo	logy Section, 10	00 SW Jackson St., Suite	420, Topeka, Kansa	s 66612-1367.
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							
			http://www.kdheks.gov	//waterwell/index	html		