

1 LOCATION OF WATER WELL: County: Harvey Fraction: 1/4 NW 1/4 NW 1/4 Section Number: 19 Township Number: 22 S Range Number: 2 E Distance and direction from nearest town or city street address of well if located within city? 1/2 W 1/2 NE Houston

2 WATER WELL OWNER: Myron Stucky RR#, St. Address, Box #: RR1 Box 134 City, State, ZIP Code: Moundridge, KS. 67107 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NW section of the top-left 4-section block]

4 DEPTH OF COMPLETED WELL: 55 ft. ELEVATION: 9-21-PP Depth(s) Groundwater Encountered: 1. 33 ft. below land surface measured on mo/day/yr Pump test data: Well water was 30 gpm Well water was 77 ft. after hours pumping Est. Yield 30 gpm Well water was 77 ft. after hours pumping Bore Hole Diameter 9 in. to 77 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped Welded Threaded 2 PVC 4 ABS 7 Fiberglass Other (specify below) Blank casing diameter 5 in. to 67 ft. Dia. 12 in. to 160 lbs./ft. Wall thickness or gauge No. 214 Casing height above land surface 12 in. weight 0.125 lb./ft. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut SCREEN-PERFORATED INTERVALS: From 67 ft. to 77 ft. From 25 ft. to 77 ft. GRAVEL PACK INTERVALS: From 25 ft. to 77 ft. From 25 ft. to 77 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole Plug Grout Intervals: From 4 ft. to 25 ft. From 25 ft. to 77 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? S How many feet? 70

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-21-180 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 180 This Water Well Record was completed on (mo/day/yr) 9-22-180 under the business name of Beckler Drilling by (signature) Paul H. Beckler

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.