	WA	TER WELL R	ECORD	Form WWC-5		2a-1212 ID N	o			
LOCATION OF WATER WELL: Fraction					Sec	tion Number	Township Numbe			
ounty: Har	vey	500	14 SE	14 5W	1/4	12	т 22	s R 2	E ∕ ₩	
stance and directi	on from nearest t	own or city stre	eet addres	s of well if locate	ed within cit	:y?				
	3 n	1. WO	f He	55404 -	1040	4 4 1	446 AUR			
WATER WELL O	WNER: 5	teve Ko	uffu	nan						
1111, Ol. Madrood, Box 11								ure, Division of Wate	r Resources	
ty, State, ZIP Code : Hesston, KS 67062						Application Number:				
LOCATE WELL'S	LOCATION WITH	4 DEPTH O	F COMPLE	TED WELL	75	ft. ELEVA	TION:			
AN "X" IN SECTI	ON BOX:	Depth(s) Gro	undwater E	Encountered 1		ft. 2	2	.ft. 3	ft.	
	 						measured on mo/day/y			
`							ter h			
NWNE Est. Yieldgpm: Well water wasft. after hours pumping										
Bore Hole Diameter 8 in. to 83ft., and in. to										
W E WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well										
Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well										
sw	SE	2 Irrigation	n 4 In	dustrial 7 Do	mestic (law	n & garden) 10	Monitoring well			
. !		Mas a shomis	al/bactoriole	orical cample cubi	mitted to De	nartmont? Vos	Noخ; الر	es mo/day/yrs sami	nle was sub-	
		mitted	al/bacterion	gicai sample subi	milled to be		Well Disinfected? Yes		No	
TYPE OF BLANK	CASING USED:		5 Wrou	ght iron	8 Concre			: Glued Clamp		
				Asbestos-Cement 9 Other (specify be			w) Welded			
7 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -			7 Fiber	Fiberglass				Threaded		
Blank casing diame		in to			in	: to	ft., Dia	in. to		
Seeing beight show	o land curface	/2 .	in waid	nt 2.4.	?	lhs /f	t. Wall thickness or ga	uge No 160		
				11 2						
TYPE OF SCREEN OR PERFORATION MATERIAL: 5 VC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)										
				Concrete tile 9 ABS			- •	12 None used (open hole)		
CREEN OR PER				5 Gauze	d wrapped		®Saw cut	11 None (ope	en hole)	
1 Continuous s		lill slot		6 Wire w		•	9 Drilled holes			
2 Louvered shu	ıtter 4 K	(ey punched	_	7 Torch	cut		10 Other (specify)		ft.	
CREEN-PERFOR	RATED INTERVA	LS: From	45	ft. to						
		From								
GRAVEL	PACK INTERVA		. 2.3	ft. to	ሃ . ጋ <i>ይ</i>	ft., From		ft. to	.π	
		From								
GROUT MATER				ent grout	_ 3 Bentor		Other			
				ft., From 🔀	<i></i> ft.		ft., From			
What is the nearest source of possible contamination:			ion:				restock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines							Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool				Sewage lagoon			12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit			•			nsecticide storage				
Direction from well	? E					How man	·			
FROM TO		LITHOLOGIC	LOG		FROM	ТО	PLUGGI	NG INTERVALS		
0 27	Rr & G	- Clay		:						
27 43	F 5a	nd + 5m	layer	-s Clay						
43 55	Br + 6	r Clay								
55 64	F Sa.									
64 75		Sm G	ravei	/						
75 77		ock								
77 83										
									70.044	
							ALL MANAGEMENT AND A STATE OF THE STATE OF T			
CONTRACTOR'S	OR LANDOWNE	R'S CERTIFIC	ATION: Th	nis water well wa	s (1) consti	ructed. (2) reco	enstructed, or (3) plugg	ed under my iurisdict	ion and was	
ampleted on (mold	av/vear)	C-2 /-/	/			and this record	d is true to the best of	my knowledge and be	elief. Kansas	
Inter Wall Castras	torie Licones No	447	•	This Water Wal	I Record w	as completed o	on (mo/day/yr) 9	-26-01		
					w	hv /eic	gnature) & Mu	ia		
nder the business		iller D	r. 11.4	1-		Dy (SI	, and a Mul			