

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Harvey</u>	<u>7 1/4 Sec 1/4 Sec 1/4</u>	<u>19</u>	T <u>22</u> S	R <u>2</u> E/W

Distance and direction from nearest town or city street address of well if located within city?

In City Walton 200 Michelle Dr.

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : <u>200 Michelle Dr.</u>	Application Number:
City, State, ZIP Code : <u>Walton, KS 67151</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>22</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>7.5</u> ft. 2. <u>10</u> ft. 3. <u>12</u> ft. WELL'S STATIC WATER LEVEL <u>10</u> ft. below land surface measured on mo/day/yr <u>2-12-02</u> Pump test data: Well water was <u>20</u> gpm. Well water was <u>20</u> ft. after <u>7</u> hours pumping <u>20</u> gpm. Est. Yield <u>20</u> gpm. Well water was <u>20</u> ft. after <u>7</u> hours pumping <u>20</u> gpm. Bore Hole Diameter <u>2.0</u> in. to <u>2.0</u> ft., and <u>7</u> in. to <u>27</u> ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. <u>X</u> No. <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter <u>5</u> in. to <u>47</u> ft., Dia			Threaded
Casing height above land surface <u>12</u> in., weight <u>12.88</u> lbs./ft. Wall thickness or gauge No. <u>214</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From <u>47</u> ft. to <u>27</u> ft., From <u>27</u> ft. to <u>27</u> ft., From <u>27</u> ft. to <u>27</u> ft., From <u>27</u> ft. to <u>27</u> ft.			
GRAVEL PACK INTERVALS: From <u>47</u> ft. to <u>27</u> ft., From <u>27</u> ft. to <u>27</u> ft., From <u>27</u> ft. to <u>27</u> ft., From <u>27</u> ft. to <u>27</u> ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>0</u> ft. to <u>20</u> ft., From <u>20</u> ft. to <u>20</u> ft., From <u>20</u> ft. to <u>20</u> ft., From <u>20</u> ft. to <u>20</u> ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
Direction from well? <u>W</u>				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				How many feet? <u>30'</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>4</u>	<u>yellow Clay</u>			
<u>4</u>	<u>64</u>	<u>yellow Shale</u>			
<u>64</u>	<u>68</u>	<u>Blue Shale</u>			
<u>68</u>	<u>75</u>	<u>White Rock</u>			
<u>75</u>	<u>76</u>	<u>Blue Shale</u>			
<u>76</u>	<u>77</u>	<u>Water</u>			
<u>77</u>	<u>87</u>	<u>Gray Shale Hard</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>2-12-02</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>7800</u> This Water Well Record was completed on (mo/day/yr) <u>2-12-02</u> under the business name of <u>Boekhuys Drilling</u> by (signature) <u>Paul H. Boekhuys</u>
--