38 WATE E	8218 R WELL		RWD 10-06	Form WWC-	5	Division	of Water	Resources; App. No.		
			ER WELL:	Fraction		Section Number Town			<u> </u>	
Coun	ty: Harve	y		NW 1/4 NW 1/4 N		36	3	T 22 S	R 2 E (W	
Distan	ice and direc	om nearest town or city st	reet address of well if loo	ated	Global Positioning Systems (decimal degrees, min. of 4 digits)					
within city? Approximately 2 miles south and 4 miles west of Hesston						Latitude: 38.101245				
2 WATER WELL OWNER: Harvey County RWD #1							Longitude: -97.500223 Elevation: unknown			
RR#, St. Address, Box # : 107 N. Walnut						Datum: NAD 83				
City, State, ZIP Code P.O. Box 124 Peabody, KS 66866							Data Collection Method: WAAS GPS Unit			
	TE WEL	L'S	4 DEPTH OF COMP		11	12	ft.			
ı	ATION	IN	Depth(s) Groundwater					ft. (3) ft,	
SECTION BOX: WELL'S STATIC WATER LEVEL not checked ft. below land surface measured								e measured on mo/o	lay/yr	
N Pump test data: Well water was not checked ft. after hours pumping									g gpm	
			Est. Yield unknown gpm: Well water was							
NW	/NE	1 1	E 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
" -		ן " ן								
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Observation Was a chemical/bacteriological sample submitted to Department? Yes No If yes,										
Sample was submitted Water well disinfected? Yes No										
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped										
(1) Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded (2) PVC 4 ABS 7 Fiberglass Threaded ✓										
(2) PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 2 in. to 7 (steel) ft., Diameter 2 in. to 99 (PVC) ft., Diameter in. to ft.										
Casing height above land surface 36 in., weight 70-PVC, 3.65-steel lbs./ft. Wall thickness or gauge No154 (both)										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Columnized Steel 6 Congrete tile 8 PM (SP) 10 Ashestos Coment 12 None word (open hole)										
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:										
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)										
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (Specify) SCREEN PERCONATED INTERVALS: From 90 ft to 100 ft From ft From ft To 100 ft From										
SCREEN-PERFORATED INTERVALS: From 99 ft. to 10							From	It. to	it.	
GRAVEL PACK INTERVALS: From 94 ft. to 1						2 ft. From ft. t			ft.	
SCREEN-PERFORATED INTERVALS: From 99 ft. to 109 ft., From ft. to From ft. to ft., From ft. to GRAVEL PACK INTERVALS: From 94 ft. to 112 ft., From ft. to From ft. to ft., From ft. to From ft. to ft., From ft. to									ft.	
6 GROU	J T MATE	RIAL	Neat Cement 2	Cement grout 3 Ben	tonite	4 Other		Bentonite Ho	leplug	
Grout Intervals: From 0 ft. to 87 ft., From ft. to ft., From 87 ft. to 94 ft.										
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specif									16 Other (specify	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel						orage 14 Abandoned water well below)				
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well None known										
		1?	LITHOLOGIC LO		low man			DI LIGODIO DI	TERMINA C	
FROM 0	TO 4	Tops		JG	FROM		Ceme	PLUGGING IN ented sand, hard	IERVALS	
4	9		brown, hard		72			brown, hard with	cemented sand	
9	23		, brown, sandy, soft				streak			
23	24		ented sand, hard		78			tan, hard		
24	39		l, coarse to fine, loos ks, brown	e, clean, with clay	87 97			dark gray, hard ented sand, hard		
39	47	Sand, coarse to fine, loose and clean			99		Sand, coarse to fine, loose, clean, with clay			
47	57	Clay, brown, hard						s, brown		
57	58	Cemented sand, hard 109						ented sand, hard		
58 61 Sand, coarse to fine, loose and clean 110 61 71 Clay, brown with sand streaks							Shale	, black, limy, hard		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-18-06 and this record is true to the best of my knowledge and belief.										
					Well Reco	ord was con	pleted or	(mo/day/year)	2-2-06	
			Clarke Well & Equip			signature)	Val	ef Wyal	0	
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone										
785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.										