63 WATER	8218 R WELL	RWD 4-06 RECORD	Form WWC-	-5	Division	of Water	Resources; App. No.				
1 LOCA	TION O	F WATER WELL:	Fraction				Township Number				
	ty: Harve		NW 1/4 NW 1/4		25		T 22 S				
		ction from nearest town or city so proximately 1 mile south an		cated				grees, min. of 4 digits)			
Hess		noximately i fille south an	u 4 miles west of		Latitude:						
		L OWNER: Harvey County R	WD #1		Longitude: -97.500289						
		ss. Box # 107 N. Walnut		Elevation: Unknown Datum: NAD 83							
	State, ZIP		966		Data Collection Method: WAAS GPS Unit						
27.004	THE STORE						dethod: WAAS GF	3 Unit			
1	TE WEI	L'S 4 DEPTH OF COMP									
	I AN ''X''	IN Depth(s) Groundwater	Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft, WELL'S STATIC WATER LEVEL Not checked ft. below land surface measured on mo/day/yr.								
1	ION BO	v. WELL'S STATIC WA	ATER LEVEL Not ch	ecked ft.	below lan	d surface	measured on mo/da	y/yr			
	N	Pump test dat	ta: Well water was No	от спеске	ft. after.		hours pumping	gpm			
х			ppm: Well water was ft. after hours pumping								
	NE	1 1			supply 8 Air conditioning 11 Injection well						
w			1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering (12) Other (Specify below)								
sw	SE		Industrial 7 Dome								
	-52	Was a chemical/bacte	riological sample subr	mitted to	Departmei	nt? Yes	No 🗸 :	If yes, mo/day/yrs			
LL	S	Sample was submitted	i	Water	well disin	fected?	Yes No	/			
5 TYPI	E OF CAS	SING USED: 5 Wrough	t Iron ° Con	orata tila		CASING	IODITS: Glued	Clamped			
(1)s	teel 3	RMP (SR) 6 Asbesto	s-Cement 9 Oth	er (specif	y below)		Welded				
(2) P	VC 4	ABS 7 Fibergla	iss				Threaded	1			
Blank cas	sing diame	e land surface 36	ft., Diameter 2 ((PVC) ii	n. to 10)1 ft.,	Diameter	in. to ft.			
Casing he	eight abov	e land surface 36	in., weight 70 PVC	, 3.65 steel	lbs./ft. Wa	all thicki	ness or gauge No.	.154 (both)			
TYPE OF	Steel	N OR PERFORATION MATE 3 Stainless Steel 5 Fibe	ERIAL: (7) PVC	9	ABS		11 Other (Specify)				
1		4 Galvanized Steel 6 Con						nole)			
_		FORATION OPENINGS ARI		,			(.1	,			
1	Continuou	s slot (3) Mill slot 5	Gauzed wrapped 7	Torch cut	9 Dri	illed holes	11 None (open ho	le)			
2	Louvered	shutter 4 Key punched 6	Wire wrapped 8	Saw Cut	10 Oth	ner (Specif	fy)				
SCREEN	I-PERFOI	RATED INTERVALS: From	101 ft. to	111	ft.,	From	ft. to	ft.			
	20.41.00	From	ft. to		ft.,	From	ft. to	ft.			
	JRAVEL	RATED INTERVALS: From From PACK INTERVALS: From From	96 It. to	114	it.,	From	it. to	It.			
(CDOI	TMATE	DIAL CONTRACTOR OF	11. 10		11.,	FIUIII	Pontonito Holo	olug			
Grout In		RIAL: 1 Neat Cement 2 From 0 ft. to	90 a Ben	itonite	4 Other		5 90	o 96 a			
1		ource of possible contamination:	It., From		It. to	It	., From	II. 10II.			
1 Septic		4 Lateral lines 7	Pit privy 10	0 Livestoc	k pens	13 Insec	cticide Storage	16) Other (specify			
2 Sewer	lines	5 Cess pool 8	Sewage lagoon 1	1 Fuel stor	rage		ndoned water well	below)			
3 Water	tight sewer	lines 6 Seepage pit 9	1 cody ara	2 Fertilize	-	15 Oil v	vell/gas well	None known			
		?		low many							
FROM	ТО	LITHOLOGIC LC)G	FROM	TO	Olav II	PLUGGING INTI				
0	1 12	Topsoil		63	67 74		ght brown, sandy a ght brown with sar				
12	15	Clay, light brown Sand, brown, fine to coars	88	74	76		ght gray and light	-			
15	20	Clay, light and dark brown		/ · · · · ·	10		s, very fine	JOWN WILL SUIT			
20	29	Clay, light brown, soft, sa		76	79		brown ,very fine to	fine			
29	32	Clay, tan and gray with sa		79	91			se with gravel, fine			
32	33	Cemented sand, clay, tan				and sh	ale				
33	36	Clay, light gray, soft		91	91.5	Cemented sand					
36	45	Clay, gray, green, firm		91.5	93	Sand, brown, fine to coarse with gravel, fine					
45	50	Clay, gray				and shale					
50	63	Clay, gray and light brown		93	94		nted sand, very har				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-2-06 and this record is true to the best of my knowledge and belief.											
			jeur)				(mo/day/year)				
1		ame of Clarke Well & Equip			ignature) 🗸		04///				
	- women	or claire well a Equip	mont, mo.	- Jy (8	-5.minic) (ne or circle the correct an				

copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.

WATE	R WELI		CORD	Form WWC	-5	Division of	of Water F	Resources; App. No.					
	ATION O		TER WELL:	Fraction NW 1/4 NW 1/4	NW 1/4	Section Nu 25	mber	Township Number T 22 S	Range Number				
Distar within	nce and dire	ection fi	rom nearest town or city str nately 1 mile south and	eet address of well if lo		Latitude:	itioning 38.11	Systems (decimal de 5819	grees, min. of 4 digits				
2 WATER WELL OWNER: Harvey County RWD #1							Longitude: -97.500289 Elevation: Unknown						
	RR#, St. Address, Box # : 107 N. Walnut City, State, ZIP Code : Pooledy KS 66866							Datum: NAD 83					
			reabody, NS 6666	66				lethod: WAAS GF	PS Unit				
1	ATE WEI	LL'S	4 DEPTH OF COMPI										
WIT	H AN ''X'		Depth(s) Groundwater WELL'S STATIC WA	Encountered (1)		ft. (2	2) Lourfood	ft. (3)	ft,				
SEC	TION BO	X:	Pump test data	a: Well water was		ft. after		hours pumping	gpm				
			Est. Yieldgpn	n: Well water was		ft. after		hours pumping	gpm				
NV	WNE-	1	WELL WATER TO B										
w		E	1 Domestic 3					-	Other (Specify below)				
sw	VSE	.	2 Irrigation 4					-	TC /1 /				
			Was a chemical/bacter						If yes, mo/day/yrs				
	S		Sample was submitted					es No	25557				
1			USED: 5 Wrought	Iron 8 Con	ncrete tile	e C.	ASING.	JOINTS: Glued	Clamped				
1 ,	DIZO	4 4 70 (P (SR) 6 Asbestos S 7 Fiberglas					Throada	d				
Blank ca	asing diam	eter	in. to surface	ft., Diameter		in. to	ft., I	Diameter	in. to ft.				
Casing h	neight abov	e land	surface	in., weight		lbs./ft. Wal	ll thickn	ess or gauge No.					
TYPE O	OF SCREE! Steel	NOR I 3 Sta	PERFORATION MATE ainless Steel 5 Fiber	RIAL: rglass 7 PVC	9	ABS	1	1 Other (Specify)					
	Brass	4 Gal	Ivanized Steel 6 Con	crete tile 8 RM (
	N OR PER Continuou		TION OPENINGS ARE 3 Mill slot 5	: Gauzed wrapped 7	Torch cut	0 Deill	lad holes	11 None (open ho	Ja)				
i			4 Key punched 6						a				
SCREE	N-PERFOI	RATEI	D INTERVALS: From	ft. to		ft., F	rom .	ft. to	ft.				
			From	ft. to		ft., F	rom	ft. to	ft.				
	GRAVEL	PACK	D INTERVALS: From From K INTERVALS: From From	ft. to		ft., F	rom	ft. to	ft.				
6 GROI	UT MATE	CRIAL	: 1 Neat Cement 2	Cement grout 3 Re	ntonite	4 Other	10111	11. 10	It.				
1	ntervals:		om ft. to	-				From					
			of possible contamination:	•	0 Livesto			icide Storage	16 Other (specify				
2 Sewe	c tank er lines				1 Fuel sto	•		doned water well	below)				
_	ertight sewer	lines				•	15 Oil w	ell/gas well					
		1?		l	low man								
FROM 94	TO 110	San	LITHOLOGIC LO		FROM	TO		PLUGGING INTE	ERVALS				
34	110		shale	e with graver, line									
110	111	-	nented sand										
111	113		le, clay, green and har	rd									
113	114	Snai	le, green, hard						1.000				
		See	first page for all other	information and									
		signa	ature										
			1.10/00/11			+							
7 CONT	TRACTOR	r'S OR	R LANDOWNER'S CER	RTIFICATION: T	his water	well was (1)	constru	cted (2) reconstru	icted (3) plugged				
under my	/ jurisdiction	and w	vas completed on (mo/day/y	rear)					dge and belief.				
	Vater Well (e business n		tor's License No.	inis water		signature) 2		mo/day/year)					
INSTRUC	TIONS: Use	typewri	iter or ball point pen. PLEASE		learly. Ple	ase fill in blank	s, underly	e or circle the correct an					
			Health and Environment, Burn TER WELL OWNER and ret						2-1367. Telephone				
				K	7-70								