WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No. 14932	
1 LOCATION OF WATER WELL:		Section Number Township No. Range Number	
County: Hodgeman	1/4 SW 1/4 SE 1/4 SW		
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here			
2 1/4 North, 1 3/4 East of Hanston		Longitude: (in decimal degrees)	
2 1/4 North, 1 5/4 Last of Hanston		Elevation:	
2 WATER WELL OWNER: Hahn Inc.		Datum: WGS 84, NAD 83, NAD 27 Collection Method:	
RR#, Street Address, Box #: 27610 NE 231 Road		GPS unit (Make/Model:)	
City, State, ZIP Code : Hanston, Ks. 67849		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey	
Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
WITH AN "X" IN 4 DEPTH OI	COMPLETED WELL 170		
SECTION BOX: Depth(s) Grou			
WELL SSIA	N WELL'S STATIC WATER LEVEL 46 ft. below land surface measured on mo/day/yr. 5/21/12 pump test data: Well water was 109' 6" ft. after 3 hours pumping 666 gpm		
EST. YIELD 783gpm. Well water was 123			
W			
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)			
Irrigation Industrial Domestic Joyen & gorden Monitoring wall			
Was a chemical/bacteriological sample submitted to Department? Yes No			
S If yes, mo/day/yr sample was submitted			
1 mile Water well disinfected? ☑ Yes □ No			
5 TYPE OF CASING USED: Steel V PVC Other			
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 16			
Casing height above land surface. 18 in., Weight Sch 40 lbs./ft., Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
☐ Steel ☐ Stainless Steel			
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:			
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)			
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 170 ft. to 90 ft., From ft. to ft.			
From			
GRAVEL PACK INTERVALS: From 170 ft. to 20 ft., From ft. to ft.			
From			
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From ft. to ft., From 20 ft., From ft., From ft.			
What is the nearest source of possible contamination:			
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)			
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well None			
Direction from well			
FROM TO LITHOLO	GIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
0 5 Top soil 5 43 Brown clay			
5 43 Brown clay 43 68 Sand & gravel- small	to med with		
streaks of soft tan clay			
68 92 Hard tan clay			
92 138 Sandstone			
138 139 Gray shale 139 169.5 Sandstone			
139 169.5 Sandstone 169.5 170 Blue gray shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged			
under my jurisdiction and was completed on (mo/day/year) .6/27//12			
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 7/5/12			
INSTRUCTIONS: Use ty pewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three conies			
(white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at			
http://www.kdheks.gov/waterwell/index.html.			
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy			