LOCATION OF WATER WELL: Fraction COUNTY: HODGE AN 1/	4 NW 1/4 NW 1/4		Township Mumber	Range Number
Distance and direction from nearest tow FROM HANSTON - 1/4 SOUTH ON COUNTY ROAD	,			
WATER WELL OWNER: HAMM, SANDY RR#, St. Address, Box # : BOX 2 City, State, ZIP code : HAMSTON, KS	67849-	Application N	umber:	of Water Resources
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL Depth(s) Groundwater Enco	75 ELEVATION: untered 1.	0 ft. 2.	0 ft. 3. 0 ft
1 NW	WELL'S STATIC WATER LEVEL	25 ft. below land ell water was 0	surface measured o	n mo/day/yr 12/12/96
\mathbf{H}	Estimated Yield 45 gpm: Bore Hole Diameter 1			•
1	WELL WATER TO BE USED AS: 0		111 0	1
1	Was a chemical/bacteriologi If yes, mo/day/yr sample wa	s submitted	to department? No Water	well disinfected? Ye
TYPE OF BLANK CASING USED: PYC Blank casing diameter 5 in. to Casing height above land surface 12 TYPE OF SCREEN OR PERFORATION MATERIAL: SCREEN OR PERFORATION OPENINGS ARE:	CASING JOINTS: 6 75 ft., Oia in. in. weight 200 lbs/ PYC SAW CUT	LUED to 0 ft., Dia ft. Wall thickness	in. to 0 or gauge No. 21	ft.
SCREEN PERFORATEO INTERVALS: F GRAYEL PACK INTERVALS: F	ron 50 ft. to 70 ft., ron 0 ft. to 0 ft., ron 25 ft. to 75 ft., ron 0 ft. to 0 ft.,	From 0 ft. to	0 ft. 0 ft. 0 ft. 0 ft.	
GROUT MATERIAL BENTOWITE Grout Intervals: From 0 ft. to What is the nearest source of possible Direction from well? WEST	25 ft From 0 ft. to	0 ft., From		. How many feet? 13
FROM TO LITH O 30 TOPSOIL CLAY 30 40 FINE SAND 40 FINE - MED SAND 50 60 COARSE SAND SMALL G 60 62 CLAY 62 70 MEDIUM SAND 70 90 HEDIUM SAND CLAY LA 90 120 GRAY CLAY	HOLOGIC LOG	FROM TO	PLUGGI	NG INTERVALS
CONTRACTOR'S OR LANDOWNER'S CERTIFICATI completed on (mo/day/year) 12/12/96 and Water Well Contractor's License No. 179 under the business name of JOE'S WELL S	d this record is true to the	best of my knowledge	e and belief. Kan	ISAS