

Houslow
KS

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

Gollar #1 PA (center)

1. Location of well: County <u>Hodgman</u> Fraction <u>C. NE SE</u> <small>1/4 1/4 1/4</small> Section number <u>27</u> Township number <u>T 22 S</u> Range number <u>R 22 W</u> <small>E/W</small>	
2. Distance and direction from nearest town or city: <u>1 mile south</u> Street address of well location if in city: <u>Hanston</u>	
3. Owner of well: <u>B & M Drilling Co</u> R.R. or street: <u>Independence Kansas</u> City, state, zip code:	
4. Locate with "X" in section below: Sketch map: 	
5. Type and color of material	
	From To
<u>Clay</u>	0 20
<u>Sandy clay</u>	20 40
<u>Gravel</u>	40 60
<u>BRock 60'</u>	
<u>20'</u>	
<u>40' sat thick</u>	
<u>in Alluvium</u>	
(Use a second sheet if needed)	
18. Elevation: Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley	19. Remarks: <u>2162</u> <u>60</u> <u>2102</u> <u>TOPO</u>
20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Myers Water Well 143</u> Business name License No. Address <u>St Bend KS</u> Signed <u>R Myers</u> Date <u>6-28-77</u> Authorized representative	

6. Bore hole dia. 8 in. Completion date 6-28-77
Well depth 60 ft.

7. Cable tool Rotary Driven Dug
 Hollow rod Jetted Bored Reverse rotary

8. Use: Domestic Public supply Industry
 Irrigation Air conditioning Stock
 Lawn Oil field water Other

9. Casing: Material Plastic Height: Above or below
Threaded Welded Surface 12 in.
RMP PVC Weight 287.3 lbs./ft.
Dia. 5 in. to 60 ft. depth Wall Thickness: inches or
Dia. 5 in. to 60 ft. depth gage No. 200

10. Screen: Manufacturer's name Self made
Type PVC Dia. 5
Slot gauge 3/8 Length 20
Set between 40 ft. and 60 ft.
ft. and 60 ft.
Gravel pack? yes size range of material 1/4 - 1/2

11. Static water level: 10 ft. below land surface Date 6-28-77
mo./day/yr.

12. Pumping level below land surfaces:
 ft. after hrs. pumping g.p.m.
 ft. after hrs. pumping g.p.m.
Estimated maximum yield g.p.m.

13. Water sample submitted: mo./day/yr.
 Yes No Date

14. Well head completion:
 Pitless adapter Inches above grade

15. Well grouted? yes
With: Neat cement Bentonite Concrete
Depth: From 0 ft. to 10 ft.

16. Nearest source of possible contamination:
ft. Direction Type
Well disinfected upon completion? Yes No

17. Pump: Not installed
Manufacturer's name
Model number HP Volts
Length of drop pipe ft. capacity g.p.m.
Type:
 Submersible Turbine
 Jet Reciprocating
 Centrifugal Other

22 22 22 22
C NE SE
1/4 1/4 1/4