


1 LOCATION OF WATER WELL: County: <u>Hodgeman</u>	Fraction <u>SE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	Section Number <u>28</u>	Township Number <u>T 22</u> <u>S</u>	Range Number <u>R 22</u> <u>EW</u>
--	---	-----------------------------	---	---------------------------------------

Distance and direction from nearest town or city street address of well if located within city?
one mile west of the town of Hanston

2 WATER WELL OWNER: Marvin Miller
RR#, St. Address, Box # :
City, State, ZIP Code : Hanston, Kansas 67849
Board of Agriculture, Division of Water Resources
Application Number: 1449

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:


4 DEPTH OF COMPLETED WELL 117 ft. ELEVATION:
Depth(s) Groundwater Encountered 1. 74 ft. 2. 74 ft. 3. 74 ft.
WELL'S STATIC WATER LEVEL 49 ft. below land surface measured on mo/day/yr 5-12-87
Pump test data: Well water was 100 ft. after 4 hours pumping 450 gpm
Est. Yield 450 gpm; Well water was 100 ft. after 4 hours pumping 450 gpm
Bore Hole Diameter 2 1/2 in. to 2 1/2 ft., and 2 1/2 in. to 2 1/2 ft.
WELL WATER TO BE USED AS:
5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes X No ; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
7 Fiberglass Threaded
Blank casing diameter 16 in. to 57 ft., Dia. 16 in. to 57 ft., Dia. 16 in. to 57 ft.
Casing height above land surface 18 in., weight 18 lbs./ft. Wall thickness or gauge No. 7
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 57 ft. to 117 ft., From 57 ft. to 117 ft.
GRAVEL PACK INTERVALS: From 10 ft. to 117 ft., From 10 ft. to 117 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 10 ft., From 0 ft. to 10 ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage none
Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	74	topsoil & clay			
74	75	sand			
75	87	clay			
87	105	sand, rock, clay strip strip			
105	110	sand-tite			
110	117	tite sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-30-87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 130 This Water Well Record was completed on (mo/day/yr) 6-10-87 under the business name of Leo Knoefler Drilling by (signature) Leo Knoefler

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4

*