	HODGENAN	; N		4 NA	1/4 SB	1/4	; sect ; <b>26</b>	ion Num	uer	Townshi			Range R 22	B
		tion from near SOUTH, 3/4 BA				address	of well	if loc	ated wit	hin city?				
RR#, St.		HANN, Box # : BOX 2 ode : HANST		67	849-				of Agri	culture, I	)ivision	of Wa	ter Res	ources
	BLL'S LOCA N SECTION		1		H OF COMPL h(s) Groun				EVATION:		2.	0 ft.	3 .	0 f
	NW	NE	-			estdata:	Well wa	ater wa	8 (	ft. after	. 0	hours	pumping	0 g
W		X	1 1		ted Yield ole Diamet		n: Well i			ft. after			pumping O ft.	, 0 g
	S <b>W</b>	SE	-		ATER TO BE						. 4. 11			1
		-			chemical/b , mo/day/y								disinf	ected? Y
Blank cas	sing diame	NG USED: PVC ter 5	in. to			i i	n. to					ft.	•	
Blank cas Casing he TYPE OF S SCREEN OF	sing diame eight abov SCREEN OR R PERFORAT ERFORATED	ter 5 e land surface PERFORATION MA ION OPENINGS A INTERVALS:	in. to 12 TERIAL: IRE: F	in., PVC SAW C rom	ft., Dia weight UT 	200 11 200 11 0 60 f	n. to bs/ft. t t., From t., From	Wall th	ickness  ft. to ft. to	O ft. O ft.		ft		
Blank cas Casing he TYPE OF S SCREEN OF	sing diame eight abov SCREEN OR R PERFORAT ERFORATED	ter 5 e land surface PERFORATION MA ION OPENINGS A	in. to 12 TERIAL: NRB: F	in., PVC SAW C	ft., Dia weight UT 40 ft. to 0 ft. to	200 11 200 11 0 60 ft	n. to bs/ft. t t., From t., From	0 0 0	ickness  ft. to ft. to	or gauge		ft. "		
Blank cas Casing he TYPE OF S SCREEN OF  GRA  GRA  GROUT MA  Grout Ins What is	sing diame eight abov screen or R PERFORAT BRFORATED AVEL PACK TERIAL tervals:	ter 5 e land surface PERFORATION MA ION OPENINGS A INTERVALS: INTERVALS: BENTONITE From 0 ft. t source of po	in. to 12 TERIAL: RE: F F F F T	in., PVC SAW C rom rom rom	### Transfer of the control of the c	60 ft 0 ft.	n. to bs/ft.  t., From t., From t., From t., From	0 0 0 0	ft. to ft. to ft. to	O ft. O ft. O ft.	io. 21	 t.	any	
Blank cas Casing he TYPE OF S SCREEN OF  GRA  GRA  GROUT MA  Grout Ins What is	sing diame eight abov SCREEN OR R PERFORATED  AVEL PACK  TERIAL tervals: the neares n froz vel  TO 1 20 40 55	ter 5 e land surface PERFORATION MA ION OPENINGS A INTERVALS: INTERVALS: BENTONITE From 0 ft. t source of po	in. to 12 ITERIAL: IRE: F F F S to Cssible LITH D5 CLAY FINE SAN	in., PVC SAW C rom rom rom con contam CLOGIC	ft., Dia weight  UT  40 ft. to 0 ft. to 25 ft. to 0 ft. to	60 ft 0 ft.	t., From t., From t., From t., From t., From t., From	0 0 0 0	ft. to ft. to ft. to	O ft. O ft. O ft. O ft.	0 f	t. How		
Blank cas Casing he TYPE OF S SCREEN OF  GRA  GROUT MA Grout In What is Cirection  FROM 0 20 40	sing diame eight abov SCREEN OR R PERFORATED  AVEL PACK  TERIAL tervals: the neares n froz vel  TO 1 20 40 55	ter 5 e land surface PERFORATION MA ION OPENINGS A INTERVALS: INTERVALS:  BENTONITE From 0 ft. t source of po 1?  01 TOPSOIL 0 05 CLAY 02 F 37 FIN-COAR	in. to 12 ITERIAL: IRE: F F F S to Cssible LITH D5 CLAY FINE SAN	in., PVC SAW C rom rom rom con contam CLOGIC	ft., Dia weight  UT  40 ft. to 0 ft. to 25 ft. to 0 ft. to	60 ft 0 ft.	t., From t., From t., From t., From t., From t., From	0 0 0 0	ft. to ft. to ft. to From	O ft. O ft. O ft. O ft.	0 f	t. How	aany	