


1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 NW 1/4 Section Number 25 Township Number T 22 S Range Number R 24 XW
 County: Hodgeman

Distance and direction from nearest town or city street address of well if located within city?
1 3/4 North of Jetmore

2 WATER WELL OWNER: Scott Kreger
 RR#, St. Address, Box # : RR2 Box 1 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Larned, Ks. 67550 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 377 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 ft. 2 140 ft. 3 1-27-05 ft.
 WELL'S STATIC WATER LEVEL 140 ft. below land surface measured on mo/day/yr 1-27-05
 Pump test data: Well water was N/A ft. after N/A hours pumping N/A gpm
 Est. Yield N/A gpm: Well water was N/A ft. after N/A hours pumping N/A gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Stock
 Was a chemical/bacteriological sample submitted to Department? Yes N/A No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes HTH No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 277 ft. Dia 5 in. to 377 ft. Dia
 Casing height above land surface 24 in., weight SDR-17 lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 357 ft. to 277 ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 377 ft. to 20 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug
 Grout Intervals: From 20 ft. to 3 ft. From ft. to ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Direction from well? South How many feet? 100
Barn

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top soil	300	340	Sandstone
3	6	Tan clay, silty	340	360	Light gray shale, little pieces
6	12	Tan clay, silty & small sand			of sandstone & some fire clay
12	40	Tan clay	360	375	Light gray shale & fire clay
40	108	Dark gray shale	375	377	Light gray shale & fire <u>XX</u> clay
108	120	Dark gray shale, hard & brittle			& dark gray shale
120	190	Dark gray shale w/streaks of brittle shale			
190	220	Dark gray shale w/streaks of cemented sand			
220	228	Light gray shale			
228	232	Soft cemented sand impergnated in shale			
232	280	Light gray shale, soft			
280	300	Light gray shale & little pieces of sandstone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-29-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 134. This Water Well Record was completed on (mo/day/yr) 3-31-05 under the business name of Rosencrantz- Bemis by (signature) Scott Kreger