

CORRECTION TO WATER WELL RECORD (WWC-5)

The following correction(s) was made to the attached WWC-5 log, in order to file the item or to rectify lacking or incorrect information.

Fraction (1/4 1/4 1/4) Section-Township-Range changed:

listed as SE NW NE, 4-22S-25E

changed to SE NW NE, 4-22S-25W

Other changes: Initial statements: _____

Changed to: _____

Comments: name Bieshaar

verification method: Written & legal descriptions; position on plat maps; and

Jetmore, Horse Thief Canyon, & Horse Thief Canyon NE initials: DRD date: 1/26/2001
1:24,000 topog. maps.

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment Bureau of Water Industrial Programs, Bldg 283, Forbes Field, KS 66620

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 COUNTY: HODGEMAN SE 1/4 NW 1/4 NE 1/4 4 T 22 S R 25 E

Distance and direction from nearest town or city street address of well if located within city?
 FROM JETMORE - 10 W. ON HIGHWAY 156 - 7 MILES NORTH

2 WATER WELL OWNER: DIESHAAR, MARY JANE
 RR#, St. Address, Box #: 2701 WEST 35TH AVE. Board of Agriculture, Division of Water Resources
 City, State, ZIP code: DENVER, CO 80211-2809 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 45 ELEVATION: 0
 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.
 WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on no/day/yr 08/25/00
 Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm
 Estimated Yield 20 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm
 Bore Hole Diameter 10 in. to 45 ft., and in. to 0 ft.
 WELL WATER TO BE USED AS: DOMESTIC
 Was a chemical/bacteriological sample submitted to department? No;
 If yes, no/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: PVC CASING JOINTS: GLOED
 Blank casing diameter 5 in. to 45 ft., Dia in. to 0 ft., Dia in. to 0 ft.
 Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC
 SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

SCREEN PERFORATED INTERVALS: From 20 ft. to 40 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 GRAVEL PACK INTERVALS: From 18 ft. to 45 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL BENTONITE
 Grout intervals: From 0 ft. to 18 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 What is the nearest source of possible contamination: NONE - NEW SITE
 Direction from well? How many feet? 0

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|----|------------------------------------|------|----|--------------------|
| 0 | 20 | 01 TOPSOIL 05 CLAY 10 FINE-MEDSAND | | | |
| 20 | 42 | 37 FIN-COAR SAND 06 SMALL GRAVEL | | | |
| 42 | 60 | 05 CLAY 07 BLUE SHALE | | | |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed under my jurisdiction and was completed on (no/day/year) 08/25/00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (no/day/yr) 08/29/00 under the business name of JOE'S WELL SERVICE, INC. by (signature) *Judith Creek*