


LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Harvey	NE 1/4 NE 1/4 NE 1/4	16	T 22 S	R 3 R/W

Distance and direction from nearest town or city street address of well if located within city?

7 miles east of Buhler

WATER WELL OWNER: Equus Beds GMD #2	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 243 Main	Application Number:
City, State, ZIP Code: Halstead, Kansas 67056	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 135 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 35.70 ft. below land surface measured on mo/day/yr 3/26/82
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 4.0 in. to 145 ft. and in. to ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Observation well</u>
	Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <u>X</u>; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No <u>X</u>

TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS	7 Fiberglass Threaded
Blank casing diameter 2.0 in. to 132 ft., Dia	in. to ft., Dia
Casing height above land surface in., weight lbs./ft.	Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement Johnson Redhead
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)	11 Other (specify) Wellpoint
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS:	From 132 ft. to 135 ft., From ft. to ft.
	From ft. to ft., From ft. to ft.
GRAVEL PACK INTERVALS:	From ft. to ft., From ft. to ft.
	From ft. to ft., From ft. to ft.

GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 5 ft., From ft. to ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well?	How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Top soil			
3	53	Clay - brown, red, tan			
53	68	Sand & Clay layers			
68	71	Clay - tan			
71	75	Sand & Clay layers			
75	86	Clay			
86	108	Sand & Gravel - white			EB-26B
108	130	Clay - tan			
130	136	Sand & Gravel - white			
136	145	Clay			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-14-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No Wichita Water Dept This Water Well Record was completed on (mo/day/yr) 10-22-81
Under the business name of Equus Beds GMD #2 by (signature)

INSTRUCTIONS: Use typewriter or ball point pen, **PLEASE PRESS FIRMLY** and **PRINT** clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.