


LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: HARVEY		N/E 1/4 N/W 1/4 N/W 1/4	17	T 22 S	R 3 EW
Distance and direction from nearest town or city street address of well if located within city? 12 mi. West of Hesston, KS					
WATER WELL OWNER: DAVE Friesen		BLACKSTONE Drilling		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box #: RR		McPherson KS.		Application Number: T83-267	
City, State, ZIP Code: Buhler, KS. 67522					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 118 ft. ELEVATION: 40 ft.			
		Depth(s) Groundwater Encountered 40 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr 7-9-83			
		Pump test data: Well water was 100 gpm: Well water was 118 ft. after hours pumping gpm			
		Bore Hole Diameter 5 in. to 11.8 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below)		Welded	
2 PVC 4 ABS		7 Fiberglass		Threaded	
Blank casing diameter 3 in. to 9.8 ft. Dia		in. to ft. Dia		in. to ft.	
Casing height above land surface 12 in. weight 1.91 lbs./ft. Wall thickness or gauge No. 19.3					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC		10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)		12 None used (open hole)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 9.8 ft. to 11.8 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 1.5 ft. to 11.8 ft. From ft. to ft.					
GROUT MATERIAL: 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 5 ft. to 15 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? West		How many feet? 75 ft			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	Top Soil			
5	11	Red Clay			
11	50	Brown Clay			
50	62	Fine Sand			
62	70	Medium Sand			
70	93	Brown Sandy Clay			
93	117	Medium Sand			
117	118	Brown Clay			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-9-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 8-16-83 under the business name of Peterson Irrigation by (signature) Mike Peterson					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

2 2

R

3

EW

SEC.

17

N/E 1/4

N/W 1/4

N/E 1/4

N/W 1/4