

1 LOCATION OF WATER WELL: County: <u>Harvey</u>		Fraction SE 1/4 SE 1/4 SE 1/4	Section Number 21	Township Number T 22 S	Range Number R 3 E
--	--	----------------------------------	----------------------	---------------------------	-----------------------

Distance and direction from nearest town or city street address of well if located within city?

6 miles No. + 1 mi EAST OF BURRTON, KS.

EB24A

2] WATER WELL OWNER: Equus Beds Groundwater Management Dist. #2
RR#, St. Address, Box # : 243 Main
City, State, ZIP Code : Halstead, Ks. 67056

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
SW	SE

S

4 DEPTH OF COMPLETED WELL: 18 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 3 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 3 ft. below land surface measured on mo/day/yr 2/21/86

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 2 gpm; Well water was ft. after hours pumping gpm

Bore Hole Diameter 5 in. to 18 ft. and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped <input type="checkbox"/>
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass		Threaded
Blank casing diameter <u>2</u> in. to <u>13</u> ft., Dia. in. to <u>13</u> ft., Dia. in. to <u>13</u> ft.				
Casing height above land surface <u>36</u> in., weight <u>CLASS 160 PSI</u> lbs./ft. Wall thickness or gauge No. <u>160 PSI</u>				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:				
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <u>13</u> ft. to <u>18</u> ft., From <u>13</u> ft. to <u>18</u> ft., From <u>13</u> ft. to <u>18</u> ft.				
GRAVEL PACK INTERVALS: From <u>10</u> ft. to <u>18</u> ft., From <u>10</u> ft. to <u>18</u> ft., From <u>10</u> ft. to <u>18</u> ft.				

6 GROUT MATERIAL: 1 Neat cement 2 ~~Cement grout~~ 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
Direction from well? NONE WITHIN 1/4 MILE How many feet?

[illegible]

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-21-86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 2-27-86 under the business name of Peterson Irrigation, Inc. by (signature) Mike Peterson

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.