

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Harvey		NW 1/4 SW 1/4 NW 1/4	5	T 22 S	R 3 E
Distance and direction from nearest town or city street address of well if located within city?					
5 mi. E, 1 1/4 N of Buhler - 10320 N Wheatstate Rd					
2 WATER WELL OWNER: Gordon Schmidt					
RR#, St. Address, Box # : 10320 N Wheatstate Rd			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Inman, KS 67546			Application Number:		
3 LOCATE WELL'S LOCATION WITH		4 DEPTH OF COMPLETED WELL 12.0 ft. ELEVATION:			
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL 38 ft. below land surface measured on mo/day/yr 6-9-03			
		Pump test data: Well water was 40 ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 10 Domestic (lawn & garden) 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing diameter 5 in. to 11.0 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 12 in., weight 160 2.29 lbs./ft. Wall thickness or gauge No. 160					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless Steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-Cement
2 Brass		4 Galvanized Steel	6 Concrete tile	9 ABS	11 Other (Specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Guazed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	ft.
SCREEN-PERFORATED INTERVALS: From 11.0 ft. to 12.0 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 2.2 ft. to 5.0 ft., From ft. to ft.					
From 5.5 ft. to 12.7 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 2 ft. to 2.2 ft., From 5.0 ft. to 5.5 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	pond
Direction from well? NE How many feet? 50					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 26 Gr clay					
26 47 Br clay					
47 65 Gr clay					
65 68 M sand					
68 82 Br clay					
82 86 F sand					
86 106 F-M sand					
106 127 M sand + Sm Gravel					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-9-03 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's Licence No 447 This Water Well Record was completed on (mo/day/yr) 7-1-03					
under the business name of Miller Drilling by (signature) E. Miller					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					