## CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

Location listed as:	County: Harvey Location changed to:
Section-Township-Range: 17-22 5-3 W	
Fraction ( 1/4 1/4 1/4):	NE NE SE
Other changes: Initial statements:	
Changed to:	
Comments:	
verification method: <u>Written &amp; legal descri</u> with GMD #2, and mapping t	iptions, communications  bool on KGS website.  initials: FRL date: 6/19/2006

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction		Section number		Township number	Range number	
1. Location of well:	Harvey	SE 1/4 SE 1/4 NE	1/4	1	7	T 22 S	R 3 E	
7 1/2 mi. north of Burrton  R.R. or street: 2.						ruus Beds GMD #2		
4. Locate with "X" in section below: Sketch map:						alstead, Ks. 67056  6. Bore hole dia. 4 in. Completion date 9/12/79		
N. Locare with A. In section below:						Well depth		
						7 Cable tool X Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary		
						8. Use: Domestic Public supply Industry		
W 1 2 E					Irrigation Air conditioning Stock			
-   ;						Lawn Oil field water X Other  9. Casing: Material Height: Above or below		
					9. Casing: Material	Height: Above or below ISurface in.		
					RMPPVC_XWeightIbs./ft.			
1 Mile ———						Dia. 2 in. to 120ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage NoSch 40		
5. Type and color of	material			From	То	10. Screen: Manufacturer's r	name	
Top so:	<del>i</del> 1			a	4	Johnson	-	
100 50.				<u> </u>		Slot/gauze 10	Dia. <u>1.25 in.</u>	
Clay re	ed - tan			4	38	Set between 120	_ft. andft.	
Layers	of fine sand & cla	ay		38	45	ft. c Gravel pack? <b>NO</b> _ Size ra		
Fine sa	and	****		45	60	11 Static water level:	mo /day/yr	
Tille So	and			45	69	ft. below land sur		
Clay ta	an			69	80	12. Pumping level below land	d surfaces: hrs.pumpingg.p.m.	
Sand medium white				80.	95	ft. after	hrs. pumping g.p.m.	
				٥٦		Estimated maximum yield — 13. Water sample submitted:		
Sand & clay layers			-	95	110	Yes X No		
Clay ta	Clay tan			110	118			
Sand medium white				118	126	Pitless adapter Inches above grade		
G1 av				300		15. Well grouted? <u>Yes</u> With: X Neat cement	Bentonite Concrete	
Clay gray				126	135	Depth: From ft. to		
						16. Nearest source of possible ft Direction		
						Well disinfected upon comple	etion? Yes X No	
				Ì		17. Pump:	X Not installed	
	*			<u> </u>		Manufacturer's name Model number	HP Volts	
				<u> </u>			ft. capacityg.p.m.	
					Type: Submersible	Turbine		
						Jet	Reciprocating	
(Use a second sheet if needed)			<u></u>	1	Centrifugal	Other		
18. Elevation:	19. Remarks:	•				20. Water well contractor's This well was drilled under n	certification: ny jurisdiction and this report	
T						is true to the best of my know	• •	
Topography: Hill	EB-30B					Business name	ds GMD #2	
Slope							Halstead, Ks.	
Upland Valley						Signed Authorized re	presentative	