		WATER W	ELL RECORD	Form WV	VC-5 K	(SA 82a-121	12		
1 LOCATION OF WA	TER WELL:	FRACTION			TION NUMBE			RANGE NU	JMBER
Harvey		NW 1/4	NE 1/4 NV	V 1/4	28	T 22	2 s	R 3W	/ E/W
1	rom nearest town or city		-						
1/4 mile So.			ast of Burmac Roa	ıd	Burr	ton, Kansas			
2 WATER WELL	OWNER: BUR	RRTON, CITY	Y OF				Decided Acc		
RR#,ST. ADDRES		. Box 100					Board of Agri	culture, Division of W	later Resource
CIT	, STATE: Buri	rton, Kansas		Z	IP CODE: 6	7020	Application Num	nber:	
3 LOCATE WELL'S		DEPTH OF COMP	PLETED WELL:	30 ft.		ELEVATION:			
WITH AN "X" IN S	D-	epth of groundwate	r Encountered:	ft	1.		ft.		ft.
		ELL'S STATIC WA				JRFACE MEASU		lav/vr: 7/29	
					W LAND S			-,,,,_,	
NW	NE			vater was		ft. after		of pumping @	gpn
W Wije		Est. Yield:		water was	20 "	ft. after		of pumping @	gpm
Z W	'	Bore Hole Diamete	,	to 3	30 ft	. and	in.	to	ft.
- SW	J_ 1	'ELL WATER TO E 1. Domestic 3.		water supply	7. Lawn	and garden only	9. Dewateri i	.8	tion well
				water supply			10. Monitorin	12. Other (Sp	ecify below
		•	eriological sample submitted		YES	NO		vhat mo/day/yr w	as sample
1 '		ubmitted	mological bampio dabilitico	о вораничени		Water Well Disinf			10
5 TYPE OF C	ASING USED:			9.0	ther (Specify	, balow) CAS	ING JOINTS:	Glued	Threaded
1. Steel	3. RPM (SI	R) 5. Wrought	t Iron 7. Fibergla			, below) CAS		Welded	Clamped
2. PVC	4. ABS	6. Asbesto	s-Cement 8. Concret	e tile SD	R-26			TOIGGU	Jianipeu
Blank casing diame	_	in. to	10 ft., Dia.	in.	to	ft.,	Dia.	in. to	ft.
	_	24							
Casing height abo		,	Weight:	ı	bs. / ft.	Wall thi	ickness or gaug	je No.	
1	OR PERFORATION		7. PVC	0.0	DC.	11 0#	nor (enocify)		
1. Steel	3. Stainless Steel	5. Fiberglass		9. A			ner (specify)		
2. Brass	4. Galvanized	6. Concrete 1	Tile 8. RMP (SF	3) 10. A	Asbestos-Ce	ment 12. No	ne used (open	hole)	
SCREEN OR PER	ORATION OPENING	GS ARE:							
1. Continuous s	ot 3. Mill sl	lot 5.	Gauzed wrapped	7. To	rch cut	9. Drille	ed holes	11. None (o	pen hole)
2. Louvered shu	ter 4. Key p	ounched 6.	Wire wrapped	8. S a	w cut	10. Othe	er (specify)		
			••				(-,,		
SCREEN - PERFO	RATION INTERVAL	From	10 ft.	to 20	ft.,	From	ft.	to	ft.
		From	ft.	to	ft.,	From	ft.	to	ft.
GRAVEL F	ACK INTERVALS:	From	ft.	to	ft.,	From	ft.	to	ft.
		From	ft.	to	ft.,	From	ft.	to	ft.
C GROUT MATE	DIAI S:				-				
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug									•
Grout Intervals: From 0 ft. to 9 ft., From ft. to ft., From ft. to ft., From ft. to ft.									ft.
1. Septic tank	4. Latera	-	7. Pit privy	10. Livestoo	ck pens	13. Insecti	cide storage	15. Oil well/G	as well
9 Sauras Israel								ecify below)	
2. Sewer lines					_	14. Abana	on water wen		
3. Watertight sev	C 41	-9- P	9. Feed yard	12. Fertilize	r storage			4 mlus	
Direction from well			0100		T ==	How ma	any feet? 30 f		
From To		LITHOLOGIC	C LOG	From	To		LITHOLO	IGIC LOG	
0 2	topsoil				 				
2 9	brown and ta								
9 12	medium sand			+	 	<u> </u>	***		
12 18 18 30	medium to co	oarse sand			 	<u> </u>			
10 30	coarse sand			_					
			· · · · · · · · · · · · · · · · · · ·		 				
	·· · · · · · · · · · · · · · · · · · ·								
			,,,,,						
7 Contractor's o	r Landowner's Certifi	ication. This water	well was 1. construct	ted 2. re	constructe	d or 3, i	plugged	under my jurisdicti	ion and
\vdash									
was completed of	n (mo/day/year)	7/29/2009	and this reco	ra is true to the	e best of my	knowledge and b	pelief.		
Kansas Water W	ell Contractor's Licen	se No. 236	This water	well record wa	as completed	d on (mo/day/yea	r) 8/17	/2009	
under the husine	ss name of Harp	Well and Pur	mn Service	by (si	ignature)	7	2.55	11 ~ . ~	
and and busine	manp	Wen and Ful	inp bei vice	J, (3		10	ruws	. Harp	