WATER V	VELL RECORD	Form W	WC-5	D	ivision of Wate	r Resources App. N	o. L	
1 LOCATION OF WATER WELL:		Fraction			on Number		Range Number	
County: Harvey		4 SW 4 SW			9 T 22 S R 3 DE G			
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					Global Positioning System (GPS) information: Latitude:			
					Elevation: Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: Equus Beds GMD 2					Collection Method:			
RR#, Street Address, Box #: 313 Spruce Street				GPS unit (Make/Model:)				
City, Sta	te, ZIP Code : Halstea	d, Kansas 67056		Est. A	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 150 ft.								
WITH AN SECTION								
SECTION	WELL'S STATIC WATER LEVEL. n/aft. below land surface measured on mo/day/yr							
Pump test data: Well water wasft. after hours pumping gpm								
EST. YIELDgpm. Well water was					ft. after hours pumping gpm			
w.	E Bore Hole Diam	teter 6						
	□ Domestic							
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ✔ No								
S If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected? ☐ Yes ☑ No								
5 TYPE OF CASING USED: Steel PVC Other .Galyanized								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter 2 in. to .7 ft., Diameter .2 in. to .140 ft., Diameter in. to ft.								
Casing height above land surface 36 in., Weight SCH.40 lbs./ft., Wall thickness or gauge No154 TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From. 150 ft. to135 ft., From ft. to ft.								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 135								
What is the nearest source of possible contamination: Neat cement benonite								
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage V Other (specify below)								
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedvard ☐ Fertilizer storage ☐ Oil well/gas well ☐ None								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
FROM TO			FROM	TO			GGING INTERVALS	
0 3	Top soil		125	140	Sm. to f.sno	d.tan cly mix 60/		
3 54	Dark tan clay		140	150	Med. sand			
54 70	Small to fine sand	N1						
70 75		Medium to small sand						
75 76		Gray clay						
76 87 87 94	Small to med. sand	Small to med. sand Bluish gray clay						
94 100		Sm.snd.blue/gry.cly mix 60/40						
100 120							H	
120 129		Tan cly. med. sand 80/20						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .1.1-2409 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No134 This Water Well Record was completed on (mo/day/year) .11-30-09								
under the business name of . Rosencrantz-Bemis Ent. by (signature) Dadaca Dadaca INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								
KSA 82a-1212 Check: [4] White Copy, [] Pink Copy								