WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: TOWNSHIP NUMBER FRACTION SECTION NUMBER RANGE NUMBER NE Harvey NE NW19 22 3W 1/4 1/4 1/4 s E/W Distance and direction from nearest town or city street address of well if located within city? 23117 SW 60th Burrton, KS. 1 1/2 mile West of S. Burmac Rd., So side of SW 60th YOUNG, Mark WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 23117 SW 60th Burrton, Kansas CITY, STATE: ZIP CODE: Application Number: <u>70</u> 3 4 DEPTH OF COMPLETED WELL: ft. ELEVATION: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. Depth of groundwater Encountered ft ft. WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/26/10 Pump test data: Well water was ft. after hours of pumping @ N₩ NE gpm Est. Yield: ft. after Φ gpm Well water was hours of pumping @ gpm Ī Bore Hole Diameter 12 in. ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE-7. Lawn and garden only 1. Domestic 3. Feedlot 5. Public water supply 12. Other (Specify below) 10. Monitoring well 8. Air conditioning 4. Industrial 6. Oil field water supply ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO submitted Was Water Well Disinfected? (YES) NO 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1 Steel Welded Clamped SDR-26 Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 55 Blank casing diameter Dia. Dia in. to ft. Casing height above land surface: 2.35 in. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS 1. Steel 3. Stainless Steel 5. Fiberglass 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 2. Brass 4 Galvanized Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 1. Continuous slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 55 70 From to ft., From ft. From ft. to ft., From ft ft. GRAVEL PACK INTERVALS: 24 ft to 70 From ft., From ft to ft. From ft to ft.. From ft. to ft **GROUT MATERIALS:** 6 Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: 4 24 From ft. ft., From ft. to ft.. From ft. What is the nearest source of possible contamination 7. Pit privy 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines Cess Pool None Yet 12. Fertilizer storage 9. Feed yard 3. Watertight sewer line 6. Seepage pit How many feet? Direction from well? LITHOLOGIC LOG From Τо LITHOLOGIC LOG From Τо topsoil clay sandy clay 15 26 fine sand 26 34 medium sand 34 45 clay 45 50 sandy clay 50 55 fine sand 55 70 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 10/26/2010 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) Todd S. Harb by (signature) under the business name of Harp Well and Pump Service