WATE	R WELL	RECORD	Form '	WWC-5	D	ivision of Wate	r		
				e in Well Use		esources App. N		Well ID	
1 LOCATION OF WATER WELL: Fraction						ection Numbe			
County: Finney						36	T 22 S	1	
Business: dir						treet or Rural Address where well is located (ifunknown, distance and irection from nearest town or intersection): If at owner's address, check here:			
Address: 5610 W. Railroad Avenue N. Highway 83 & W. North Shore Cir. 1568' West, 160' South									
City: Holcomb State: KS ZIP: 67851									
3 LOCATE WELL WITH "X" IN 4 DEPTH OF COMPLETED WELL:215 ft. 5 Latitude:									
SECTION BOX. Depth(s) Groundwater Encountered: 1)							tude:	(decimal degrees)	
SECTI	2)							84 NAD 83 NAD 27	
	1			, measured on (mo-day			e for Latitude/Longitud	<u>e</u> :)	
- NW -	above land surface, measured on (mo-day-yr						(WAAS enabled? [-	
	Pump test data: Well water was150 ft.						and Survey Topog		
W	E after5 hours pumping 36g								
SW -	SE	ofter.		vater was					
	after hours pumpinggg					6 Eleva	tion:	R. Ground Level TOC	
	S Bore Hole Diameter:10 in. to215					ft. and Source: Land Survey GPS Topographic Map			
	mile			in <u>to</u>	ft.		Other		
7 WELL WATER TO BE USED AS:									
1. Domesti				ater Supply: well ID					
	Household 6. □ Dewatering: how many wells? 7. □ Aquifer Recharge: well ID								
	Livestock 8. Monitoring: well ID								
	2. Irrigation 9. Environmental Remediation: well ID					a) Closed Loop Horizontal Vertical			
	3. Feedlot Air Sparge Soil Vapor Ext								
4. Indus			Recovery						
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ■ No If yes, date sample was submitted:									
Water well disinfected? ■ Yes □ No									
8 TYPE OF CASING USED: Steel PVC Other									
Casing height above land surface 15 in. Weight 200 lbs./ft. Wall thickness or gauge No. SDR21									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)									
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)									
SCREEN-PERFORATED INTERVALS: From175 ft. to .215 ft., From ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From									
9 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other									
Grout Inter	rvals: From .	5 ft. to	25	ft., From1.10	ft. to13	30 ft., From	ft. to	ft.	
Nearest so		ble contaminati	on: Lateral Line	Dia Deire		Livestock Pe	Impost	icide Storage	
Sewe			Cess Pool	es Pit Privy Sewage La		Fuel Storage		doned Water Well	
□ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well									
Other (Specify) Direction from well? West Distance from well? 700 ft.									
Direction f				Distance from w					
0	2		HULU	GIC LUG	FROM			or PLUGGING INTERVALS	
2	27	Top Soil Brown Clay			173		Cemented Sand S	With Brown Clay and	
27	40	Fine Sand			187		Fine To Med. Sand		
40	95		Brown Clay Few Gypsum Streaks			-	Med. Sand With W		
95	106		Med. Sand Small Gravel, Few Cem Str.				Yellow Soap Stone		
106	123	Brown Clay					2300 230110		
123	143		Brown Clay With Med. Sand Streaks						
143	143 163 Med. To Coarse Sand Small Gravel								
163 173 Med. Sand With Brown Clay Streaks									
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged									
under my jurisdiction and was completed on (mo-day-year) .8-16-22									
under the business name of Midwest Well. & Pump Inc									
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,									
				66612-1367. Mail one to			ne for your records. Telep		
Visit us at h	ttp://www.kdhe	ks.gov/waterwell/i	ndex.html		KSA 82a-	1212		Revised 7/10/2015	