		WATER V	VELL RECORD F	orm WWC-5	KSA 82	a-1212			
1 LOCATION OF WA	TER WELL:	Fraction			tion Number	Township Nur	nber	Range Number	
CountyKEARNY		NE 1/4 N			.8	Т 22	S	R 38 E/W	
Distance and direction			ess of well if located	within city?					
13 MILES NOR									
2 WATER WELL OV	VNER: ROGER B	ARNHARDT							
RR#, St. Address, Bo	x # : BOX Q					Board of Ag	riculture, D	ivision of Water Resource	
City, State, ZIP Code : LAKIN, KANSAS 67860					Application Number:				
LOCATE WELL'S L	OCATION WITH	DEPTH OF COM	IPLETED WELL. 27.	0	ft. ELEV	ATION:			
→ AN "X" IN SECTIO	N								
	I X	WELL'S STATIC W	ATER LEVEL . 18	7 ft. t	elow land su	rface measured on r	no/day/yr	.8-3.1-94	
	NE	Pump te	st data: Well water	was	ft. a	after	hours pur	mping gpn	
1 1/4/	146 - 146 -	Est. Yield	. gpm: Well water	was	ft. a	after	hours pur	mping gpn	
<u> </u>	de la company de	Bore Hole Diameter	in. to .		ft.,	and	in.	to	
E W SEEDING EXCELLENCE CONTROL OF STREET, STRE		WELL WATER TO	BE USED AS: $1-6$	Public water	er supply			njection well	
1 SW	SE	(Domestic)			ter supply			Other (Specify below)	
1 mm 244 mm mm		2 Irrigation			-				
		Was a chemical/bac	teriological sample su	ubmitted to D	•			mo/day/yr sample was su	
do .	5	mitted	and and are the control of the contr		W	ater Well Disinfected			
5 TYPE OF BLANK	CASING USED: 1	5	Wrought iron	8 Concr	ete tile	CASING JOIN	ITS: Glued	I Clamped	
(1 Stee)	3 RMP (SR	6	Asbestos-Cement		(specify belo	,		∍d	
2 PVC	4 ABS		Fiberglass					ded	
								in. to fi	
Casing height above	land surface60	. BELOWin.	, weight		Ibs	./ft. Wall thickness o	gauge No	D	
TYPE OF SCREEN OR PERFORATION MATERIAL:			7 PVC 10 Asbesto				stos-ceme	nt	
1 Steel	3 Stainless	steel 5	5 Fiberglass 8 RMP (SR)					<i>N</i> .A	
2 Brass	4 Galvanize	Concrete tile	9 AE	9 ABS 12 None used (open hole)					
SCREEN OR PERFO				d wrapped		8 Saw cut		11 None (open hole)	
1 Continuous sl			6 Wire w			9 Drilled holes	a 0 K		
2 Louvered shu		y punched	7 Torch		e			ن	
SCREEN-PERFORAT	ED INTERVALS:							j	
								0	
GHAVEL PA	ACK INTERVALS:							of o f	
C COOLT MATERIA	L. 2 (Nost o	VIII 1000			ft., Fro				
6 GROUT MATERIA Grout Intervals: Fro	L. Z U Neal C	ft to	ft From	3 Deni	to 4	ft From		ft. to	
			10., 110111	, , , , , , , , , , , , , , , , , , , ,				bandoned water well	
What is the nearest source of possible contamination: Septic tank? 4 Lateral lines			7 Pit privy			Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool			8 Sewage lagoon		•			ther (specify below)	
3 Watertight sewer lines 6 Seepage pit			9 Feedyard	•	13 Insecticide storage				
Direction from well?	•	-95 p				any feet? 45			
FROM TO		LITHOLOGIC LC	G	FROM	то		JGGING II	NTERVALS	
				270	187	SAND	107907		
				187	8	CLAY/SUBSOII	٠		
				8	5	CEMENT			
							Annal Annal of Parts		
						w,			
AA-MAA									
								2013 AVIDA	
					<u> </u>				
7 CONTRACTOR'S	OR LANDOWNER	S CERTIFICATION	N: This water well wa	s (1) constr	ucted, (2) red	constructed, or (3) p	ugged unc	der my jurisdiction and w	
								owledge and belief. Kansı	
Water Well Contracto									
under the business n						ature) Kor C			
INSTRUCTIONS: Use	typewriter or ball point p	oen. PLEASE PRESS FIRM	<i>ILY</i> and <i>PRINT</i> clearly. Plea	ase fill in blanks	underline or circ	cle the correct answers. Se	end top three	copies to Kansas Department	
of Health and Environ	ment, Bureau of Water,	Topeka, Kansas 66620-0	001. Telephone: 913-296-58	545. Send one to	WATER WELL	OWNER and retain one for	your records	3.	