

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No. []

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 SW 1/4 Section Number 16 Township Number T 22 S Range Number R 4 W
County: Reno
Distance and direction from nearest town or city street address of well if located within city? 201 N Main St, Buhler, KS 67522
Global Positioning System (decimal degrees, min. of 4 digits)
Latitude: N 38.13593°
Longitude: W 97.77110°
Elevation: RIM: 1481.79; TOC: 1481.49
Datum: WGS84
Data Collection Method: legal survey

2 WATER WELL OWNER: KDHE
RR#, St. Address, Box # : 1000 SW Jackson Blvd
City, State, ZIP Code : Topeka KS
3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:
4 DEPTH OF COMPLETED WELL 25.10 ft. MW2
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
WELL'S STATIC WATER LEVEL 17.09 ft. below land surface measured on mo/day/yr 7/3/13
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yrs
Sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)
2 PVC 4 ABS 7 Fiberglass
Blank casing diameter 2 in. to 10.10 ft., Dia in. to ft., Dia in. to ft.
Casing height below land surface 0.30 ft., Weight lbs./ft. Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 10.10 ft. to 25.10 ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 8 ft. to 25.45 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-1 feet
Grout Intervals From 1 ft. to 8 ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below)
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well
Direction from well? NA How many feet? NA

Table with columns FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS.
FROM 0 TO 0.5 Concrete
FROM 0.5 TO 25.45 Brown silty clay
Flushmount waiver from BOW

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/2/13 and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 757 This Water Well Record was completed on (mo/day/year) 7/23/13 under the business name of Larsen & Associates, Inc. by (signature)

INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.