

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>	<u>NE 1/4 SE 1/4 NW 1/4</u>	<u>30</u>	<u>T 22 S</u>	<u>R 5</u> EW

Distance and direction from nearest town or city street address of well if located within city?
1/2 mi N of Hutch - 5105 Sequoia

2 WATER WELL OWNER: Tim Lacky
 RR#, St. Address, Box # : 4500 PinOak Rd
 City, State, ZIP Code : Hutch, KS 67502
 Board of Agriculture, Division of Water Resources
 Application Number: _____

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>3.2</u> ft. ELEVATION:
--	---

N
--NW--X--NE--
W E
--SW-- --SE--
S

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 5 ft. below land surface measured on mo/day/yr 5-10-05

Pump test data: Well water was 30 ft. after 2 hours pumping 2.2 gpm

Est. Yield 2.2 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

<input type="radio"/> Domestic	<input type="radio"/> 3 Feedlot	<input type="radio"/> 6 Oil field water supply	<input type="radio"/> 9 Dewatering	<input type="radio"/> 11 Injection well
<input type="radio"/> 2 Irrigation	<input type="radio"/> 4 Industrial	<input type="radio"/> 7 Domestic (lawn & garden)	<input type="radio"/> 10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
<input checked="" type="radio"/> PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter 5 in. to 12 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 18 in., weight 2.29 lbs./ft. Wall thickness or guage No. 160

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	<input checked="" type="radio"/> PVC	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)	11 Other (Specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	<input checked="" type="radio"/> Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 12 ft. to 3.2 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 10 ft. to 43 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite 4 Other

Grout Intervals: From 3 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	<input checked="" type="radio"/> Other (specify below)
			13 Insecticide storage	<u>open field</u>

Direction from well? _____ How many feet? _____

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	F Sandy silt			
4	8	Br + Gr Clay			
8	26	F Sand			
26	34	Br + Gr Clay			
34	38	Rocky Br Clay			
38	42	Br Clay			
42	43	Redish Br Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-10-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 447 This Water Well Record was completed on (mo/day/yr) 5-29-05 under the business name of Miller Drilling by (signature) [Signature]