

		RECORD		WWC-5	123	4824		sion of Wate					
			e in Well Use			Resources App. No.			Wel				
1 LOCATION OF WATER WELL:			Fraction	/ 1/	Section Nu		1						
Count	1/4 1/4	1	/4 <sup>1</sup> /4	-			T S	R	$\Box E \Box W$				
2 WELL Business: Address: Address: City:	First: ZIP:		Street or Rural Address where well is located (if unknown, dista direction from nearest town or intersection): If at owner's address, check										
3 LOCAT	E WELL		State:										
WITH "		<b>D WELL:</b> ft.			5 Latitude:(decimal degrees)								
SECTIO	ON BOX:	BOX:         Depth(s) Groundwater Encountered: 1)           2)								e:			
I	N 2) II. 5) II., of 4) 1									WGS 84 🗌 NAD		NAD 27	
			below land surface, measured on (mo-day-yr)							Latitude/Longitude:		``	
	NE		above land surface, measured on (mo-day-yr)						□ GPS (unit make/model:) (WAAS enabled? □ Yes □ No) □ Land Survey □ Topographic Map				
			Pump test data: Well water was ft.										
w	E	~	after hours pumping gpm					$\Box$ Online Mapper:					
SW	SE		Well water was ft.										
3₩			after hours pumping gpm					6 Fleve	tion	. ft	Groun	d Level 🗖 TOC	
	S S		Estimated Yield:gpm Bore Hole Diameter:in. tof					6 Elevation:ft. □ Ground Lev Source: □ Land Survey □ GPS □ Topog					
	-	Dole Hole L											
	1 mile  in. to ft. □ Other												
1. Domestic				ter Supply we	ID			10. 🗆 Oi	] Fie	d Water Supply le	ase		
			<ul> <li>5. Dublic Water Supply: well ID</li> <li>6. Dewatering: how many wells?</li> </ul>										
_	—			Recharge: well ID						I Uncased Geotechnical			
Livest	Livestock 8. Monitoring: well ID						12. Geothermal: how many bores?						
	. Irrigation 9. Environmental Remediation: well ID									Loop 🔲 Horizonta			
3. 🗌 Feedlot				-			ı	b) Open Loop  Surface Discharge  Inj. of Water					
4. 🗌 Indust			Recovery							specify):			
Was a chemical/bacteriological sample submitted to KDHE?  Yes No If yes, date sample was submitted:													
Water well disinfected?  Yes No													
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded													
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft.													
Casing height above land surface													
	TYPE OF SCREEN OR PERFORATION MATERIAL:         Steel       Fiberglass         PVC       Other (Specify)												
☐ Steel □ Brass		inless Steel	☐ Fiber		PVC	used (one)	hola)		ier (S	pecify)	•••••		
□ Brass □ Galvanized Steel □ Concrete tile □ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:													
	nuous Slot	☐ Mill Slot		auze Wrapped	ПΤ	Forch Cut	🗆 Dri	illed Holes		Other (Specify)			
		Key Punch						one (Open H		(-F),			
SCREEN-I	PERFORAT	ED INTERVA	ALS: From	1 ft. to	)	ft., F1	om	ft. to	o	ft., From	ft. to	) ft.	
G	RAVEL PA	CK INTERVA	ALS: Fron	1 ft. to	)	ft., Fi	om	ft. to	o	ft., From	ft. to	) ft.	
				. ft., From		. ft. to		ft., From		ft. to	ft.		
		ole contaminati			ъ ·		<b>—</b> •						
□ Septic □ Sewer			ateral Line Cess Pool	s ☐ Pit □ Sev		0.000 <b>n</b>		livestock Pe Fuel Storage		☐ Insectic			
	ight Sewer L		beepage Pit					Fertilizer Sto					
								ertilizer 5to	nage		ii/Gas wei		
										ft.			
10 FROM	ТО	L	ITHOLOG	GIC LOG		FRO	М	TO	LIT	HO. LOG (cont.) or	PLUGGIN	JG INTERVALS	
						Notes	s:						
11 001	DACTOR	CODIAND		CEDTIEIC	A 1710								
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo day year)													
Kansas Wa	under my jurisdiction and was completed on (mo-day-year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No												
under the business name of													
	Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each <u>constructed</u> well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.												
-		and Environment,		vater, Geology Se	ection, 1	1000 SW Jac	ckson S	t., Suite 420,	Tope	ka, Kansas 66612-136		ne 785-296-3565. SA 82a-1212	