



Corrected

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

[ ]

Well ID

[ ]

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL:

County: Reno

Fraction SE 1/4 NW 1/4 SW 1/4 SW 1/4

Section Number 27

Township Number T 22 S


Range Number R 5 E W

2 WELL OWNER: Last Name: Anderson First: Paul

Business: Address: 4500 Scotty Lane City: Hutchinson State: KS ZIP: 67502

Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: [ ]

3 LOCATE WELL WITH 'X' IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 102 ft. Depth(s) Groundwater Encountered: 1) 76 ft. 2) ... 3) ... or 4) Dry Well WELL'S STATIC WATER LEVEL: 37 ft. below land surface, measured on (mo-day-yr) 3/24/2020 Pump test data: Well water was 45 ft. after 2 hours pumping 20 gpm ... Estimated Yield: 35 gpm Bore Hole Diameter: 9.5 in. to 107 ft. and ...

5 Latitude: 38.10310 Longitude: 97.86577 Datum: WGS 84 NAD 83 Source for Latitude/Longitude: GPS (unit make/model) Land Survey Topographic Map Online Mapper

6 Elevation: 1629 ft. Ground Level TOC Source: Land Survey GPS Topographic Map Other KOLAR

7 WELL WATER TO BE USED AS:

- 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial Public Water Supply Dewatering Aquifer Recharge Monitoring Environmental Remediation Air Sparge Soil Vapor Extraction Recovery Oil Field Water Supply Test Hole Geothermal Closed Loop Open Loop Surface Discharge Inj. of Water Other

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 5 in. to 102 ft. Diameter 13 in. Weight SDR26

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Brass Galvanized Steel PVC None used (open hole) Other (Specify)

SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 82 ft. to 102 ft. GRAVEL PACK INTERVALS: From 23 ft. to 107 ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 3 ft. to 23 ft.

Nearest source of possible contamination: Septic Tank Sewer Lines Watertight Sewer Lines Lateral Lines Cess Pool Seepage Pit Pit Privy Sewage Lagoon Feedyard Livestock Pens Fuel Storage Fertilizer Storage Insecticide Storage Abandoned Water Well Oil Well/Gas Well Direction from well? SW Distance from well? 135 ft.

Table with columns: 10 FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows: 0-6 Silty F Sand, 6-34 Gr Clay, 34-76 Sandy Br & Gr Clay, 76-102 F Sand, 102-107 Br & Gr Clay. Includes a Notes section.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 3/24/2020 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 447 This Water Well Record was completed on (mo-day-year) 3/30/2020 under the business name of Miller Drilling