		L RECURD	FORM WWC-	<sub>-</sub>		r Resources App. No		
1 LOCATION OF WATER WELL:					Section Number 16	Township No.		
County: Reno NE ¼ SW ¼ NE ¼ NW ¼  Street/Rural Address of Well Location; if unknown, distance & direction							R 6 □E ☑W	
				Global Positioning System (GPS) information:  Latitude: .38,14.125				
from nearest town or intersection: If at owner's address, check here							(in decimal degrees)	
					Elevation: 1541			
					Datum: ☐ WGS 84, ☐ NAD 83, ☑ NAD 27			
2 WATER WELL OWNER: Charles H. and Terry J. Wall					Collection Method:			
RR#, Street Address, Box #: 2903 West 82nd Avenue					GPS unit (Make/Model: Garmin )			
City, State, ZIP Code : Hutchinson, Kansas 67502					☐ Digital Map/Photo,			
3 LOCATE WELL								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 50 ft.								
SECTION BOX:  Depth(s) Groundwater Encountered (1)						3) ft.		
020.	N WELL'S STATIC WATER LEVEL. 5				below land surface measured on mo/day/yr11-9-09			
		Pump	test data: Well water was	ata: Well water wasft. after hours pumping gpm				
	• V N	POT MIELD	EST. YIELDgpm. Well water wasft. after hours pumping gpm					
w N	v N		Bore Hole Diameter 28					
WELL WATER TO BE USED AS: Public water supply Geothe							njection well	
□ Domestic □ Feedlot □ Oil field water supply □ Dewatering □ Other (Specify below)								
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No								
S If yes, mo/day/yr sample was submitted								
Water well disinfected?								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: ☑ Glued ☐ Clamped ☐ Welded ☐ Threaded								
Casing diameter .16 in. to .27 ft., Diameter in. to ft., Diameter in. to ft.								
Casing height above land surface. 24 in., Weight SCH 40 lbs./ft., Wall thickness or gauge No500								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)								
From								
GRAVEL PACK INTERVALS: From								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From .15								
What is the nearest source of possible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ Direction from well ☐ Distance from well Distance from well ☐ Distance from well Di								
	T	n wellLITHOLOG					GGING INTERVALS	
FROM	TO		IC LOG FRO	JIVI	TO LITHO. L	od (cont.) or PLU	GOING INTERVALS	
0	3	Sandy top soil						
3	8	Brown clay				·		
8	15	Med. snd. gray cly. mix						
15	40	Med. sand						
49	50	Tan red clay						
ļ				-+				
T CONTRICTORIS OF LANDOWNIEDIS OFFICIALISM TILL TO THE TOTAL THE T								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   Constructed, □ reconstructed, or □ plugged								
under my jurisdiction and was completed on (mo/day/year) .11:9-09								
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 11-13-09 under the business name of								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone	785-296-	5522. Send one copy to WAT	ER WELL OWNER and retain or	ne for yo	our records. Include fe	e of \$5.00 for each c	onstructed well. Visit us at	
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy								