WATER WELL R	ECORD	rorm wy	WC-3	Division of Wat	er Resources App. N	0	
1 LOCATION OF WATER WELL:		Fraction		Section Number		Range Number	
County: Reno		NE ¼ SW ¼ NW		33		R6 □E ☑W	
Street/Rural Address of Well Location; if unknown, distance & direction				Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here . Latitude: .38,097.73							
				Longitude: 097.99398 (in decimal degrees)			
				Elevation:			
2 WATER WELL OWNER: City of Hutchinson				Datum: ☐ WGS 84, ☐ NAD 83, ☑ NAD 27			
Sity of Materialist				Collection Method: GPS unit (Make/Model: Garmin csx)			
at a man a t				☐ Digital Map/Photo, ☑ Topographic Map, ☐ Land Survey			
City, State, Zir Co	· Hutchin	son, Kansas 67501		Est. Accuracy: $\square < 3$ m, $\square 3-5$ m, $\square 5-15$ m, $\square > 15$ m			
3 LOCATE WELL							
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL .30 ft.							
SECTION BOX:							
N	WELL S STATIC WATER DEVELORMENT COLON MINE SERMO MONDERO ON MOVELY/JT						
Pump test data: Well water wasft. after hours pumping gpm							
EST. YIELDgpm. Well water wasft. after hours pumpinggp							
w NW NE	ter 1.4 in. to .30 ft., andin. to						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
Industrial □ Domestic-lawn & garden □ Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No							
S If yes, mo/day/yr sample was submitted							
Water well disinfected? ☐ Yes ☑ No							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter .8 in. to .10							
Casing height above land surface. 18. in., Weight SCH.40. lbs./ft., Wall thickness or gauge No332.							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel PVC ☐ Other (Specify)							
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
From							
GRAVEL PACK INTERVALS: From							
From							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From .10 ft. to .0 ft., From							
What is the nearest source of possible contamination:							
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ✓ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well							
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well							
Direction from well south Distance from well .20.							
FROM TO	LITHOLOG		FROM			GGING INTERVALS	
0 4 Clay	· · · · · · · · · · · · · · · · · · ·						
	& Gravel Coarse	-Med. to I ra			*		
	Shale	Mica. to Liq.					
	<u> </u>						
			 				
						-	
							
							
7 CONTRA CEORS	OD I ANDOMNIE	O'C CEDTIEIC ATION	Ve This	r wall was [7] asset		noted or Clubsed	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged							
under my jurisdiction and was completed on (mo/day/year) .11:24:09 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 11-25-09							
under the business name of Rosencrantz-Bemis Ent. by (signature) June Dolland Dolland Dolland INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
						constructed well. Visit us at	
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy							