WATE	R WEI	L RECORD	Form W	WC-5	Division of Wate	r Resources App. No),	
1 LOCATION OF WATER WELL:			Fraction		Section Number Township No.		Range Number	
			SW 1/4 SE 1/4 SV		2	T 22 S		□E Ø W
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here .					Global Positioning System (GPS) information: Latitude: .38.15956			
2 WATER WELL OWNER: Gene Vieyra					Datum: ☐ WGS 84, ☐ NAD 83, ☑ NAD 27 Collection Method:			
RR#, Street Address, Box #: 821 Dull Knife					☐ GPS unit (Make/Model: Garmin csx)			
City	, State, Z	IP Code : Hutchin	son, Kansas 67502	2	☐ Digital Map/Photo, Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL								
	H AN "X FION BO							
N WELL'S STATIC WATER LEVEL21ft. below land surface measured on mo/day/yr11-110								-10
Pump test data: Well water wasft. afterhours pumping EST. YIELDgpm. Well water wasft. afterhours pumping								gpm
w N	W N	E Bore Hole Diam	eter 1.4in. to					
		WELL WATER	TO BE USED AS: Public water supply Geothermal Injection well					
SW SE Invication			☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify be ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well heat pump-lawn					ify below) -lawn
Was a chemical/bacteriological sample submitted to Department? Yes V No								
S If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected? ✓ Yes □ No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .5								
Casing traineter 9. It., Diameter III. to 199. It., Diameter III., Diameter III. to 199. It., Diameter III. III. to 199. It., Dia								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From50								
From								
GRAVEL PACK INTERVALS: From 80 ft. to 21 ft., From ft. to ft.								
From								
Grout Intervals: From .21								
		est source of possible conta			——————————————————————————————————————		('6 1	1 \
Septic tank								elow)
✓ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
FROM	tion from	n well West LITHOLOG	ICLOG	Distance FROM	from well1.7' TO LITHO. LO	OG (cont.) or PLU	CCINC IN	TEDVALO
0	7	Sandy top soil	10.100	FRON	TO LITTO, LA	or (com.) or PLU	OOHO IN	IERVALS
7	45	Fine sand & tan clay m	ix w/ streaks					
	00	of fine sand						
45	63	Tan clay & fine sand m						
63	80	Tan clay & fine sand m of fine sand	ix w/ streaks	-				
		J. mio dand					······································	
			· · · · · · · · · · · · · · · · · · ·					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .11-1-10 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 11-12-10								
under the business name ofRosencrantz-Bemis Ent. by (signature)								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								