WATE	R WEL	L RECORD	Form W	WC-5	Divis	sion of Wate	r Resources App. N	o	
1 LOCATION OF WATER WELL: County: Reno			Fraction SE ¼ SW ¼ SW	/ ¼ SW ¾		Number 12	Township No. T 22 S	Range Number R 6 ☐E ☑W	
				Global Positioning System (GPS) information:					
	Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					Latitude: 38.14453 (in decimal degrees)			
i						Longitude: 097.93848 (in decimal degrees)			
Fror	From 82nd and Monroe 1/8E NSR					Elevation: 1674			
						<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, [NAD 27			
2 WATER WELL OWNER: Terry Dauber					Collection Method:				
RR#	, Street A	ddress, Box #: 503 Clov	verdale	GPS unit (Make/Model: Garmin csx					
City, State, ZIP Code : Hutchins			son, Kansas 67501	☐ Digital Map/Photo, ☑ Topographic Map, ☐ Land Survey					
Est. Accuracy:									
3 LOCATE WELL									
	H AN "X"								
SECI	TION BOX N								
	WELL 3 STATIC WATER ELVEL								
	Pump test data: Well water was								
	EST. YIELDgpm. Well water was								
W	W E Bore Hole Diameter 1.0								
	1	· · · · · · · · · · · · · · · · · · ·						injection well	
SWSE ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)									
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well stock Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No									
	S						ies VINO		
water well districted: [y 165] 100									
5 TYPE OF CASING USED: Steel V PVC Other									
		S: 🗹 Glued 🔲 Clam							
Casing diameter .5. in. to .50. ft., Diameter in. to ft., Diameter in. to ft.									
Casing height above land surface 16 in., Weight 160 lbs./ft., Wall thickness or gauge No214									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ☐ Other (Specify)									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)									
From									
GRAVEL PACK INTERVALS: From 80 ft. to22 ft., From ft. to									
From									
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Other									
Grout Intervals: From .22									
What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)									
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well									
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well									
		well		Distance 1	from well	-			
FROM	ТО	LITHOLOG	IC LOG	FROM				GGING INTERVALS	
0	10	Sandy top soil							
10		Tan clay and fine sand	mix				-		
22		Tan clay fine sand mix							
		fine sand	···						
55		Tan clay fine sand mix							
	 			1					
	 			 	- 1				
	 		.						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year) .8-29-11 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 134. This Water Well Record was completed on (mo/day/year) 9-6-11.									
under the business name of Rosencrantz-Bemis Ent by (signature)									
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies									
		Kansas Department of Health							
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at									
http://www.kdheks.gov/waterwell/index.html.									
KSA 82a-1212 Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy									