


1 well of 7 well manifold system
WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Reno		SE 1/4 SW 1/4 NW 1/4	36	T 22 S	R 7 NW
Distance and direction from nearest town or city street address of well if located within city? Approx. 3 miles south and 2 1/4 mi. east of Nickerson, KS					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number: n/a			
City, State, ZIP Code :		Hutchinson, KS 67501			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 23 ft. ELEVATION: Unknown			
		Depth(s) Groundwater Encountered 1. 7 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 7 ft. below land surface measured on mo/day/yr 8/31/83 Pump test data: Well water was not ok; d. ft. after hours pumping gpm Est. Yield 958/7. wells Well water was ft. after hours pumping gpm Bore Hole Diameter. 20 in. to 23 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes X No; If yes, mo/day/yr sample was submitted 5-19-83 Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded X			
2 PVC 4 ABS		Threaded			
Blank casing diameter 10 3/4 in. to 11 ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface 12 in., weight 21.15 lbs./ft. Wall thickness or gauge No. 188					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) Doerr Bridge Slot					
SCREEN-PERFORATED INTERVALS: From 11 ft. to 23 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 23 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage XXX River					
Direction from well? Northeast		How many feet? 1400			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0	40	Topsoil & Brown clay			
4	20	Sand & gravel			
20	21	Sand & gravel & thin clay streak			
21	23	Sand & gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-31-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 9/29/83 under the business name of Clarke Well & Eq., Inc. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					