WATE:	R WEI	LL RECORD	Form WW	C- 5		r Resources App. No	o. L	
1 LOCATION OF WATER WELL:		Fraction		Section Number	Township No.	Range Number		
County: Reno			NE ¼ NE ¼ SE ½		9	T 22 S	R 7 □E ☑W	
		Address of Well Location;			Global Positioning System (GPS) information:			
from	nearest t	own or intersection: If at	owner's address, check he	Latitude: .38.15552 (in decimal degrees)				
					Longitude: 098.09686 (in decimal degrees)			
				Elevation: 1601 Datum: WGS 84, NAD 83, NAD 27				
2 WATER WELL OWNER: Sharon Hathaway					Datum: WGS 84, NAD 83, V NAD 27 Collection Method:			
RR#, Street Address, Box #: 2 N. Mo					GPS unit (Make/Model: Garmin csx			
Ct. Ct. TIP C 1			on, Kansas 67561		Digital Man/Photo. 7 Topographic Map. Land Survey			
Nickers			on, Kansas 07501		Est. Accuracy:			
3 LOCATE WELL								
WIT	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 30 ft.							
SECT	Depth(s) Groundwater Encountered (1)							
	N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr10-1.3-10							
Pump test data: Well water wasft. after hours pumping								
NV	v] N		gpm. Well water was					
w	*	E Bore Hole Diam	er 9in. to .30ft., andin. toft.					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well								
[☐ Irrigation	bacteriological sample su	hmitted to	Department?	Vec V I No	***************************************	
	s		day/yr sample was submi			ICS WINO		
l	1 mile				••••••			
water will disintected. [2] 103 [2] 100								
		SING USED: Stee				•••••		
CASIN	G JOINT	S: 🗹 Glued 🗌 Clar	nped 🗌 Welded 🔲	Threaded		_		
Casing diameter .5 in. to .20 ft., Diameter in. to ft., Diameter ft.								
Casing height above land surface16								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
Steel Stainless Steel PVC Other (Specify)								
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot								
□ Louvered shutter □ Key punched □ Wire wrapped □ Saw cut □ Other (specify)								
SCREEN-PERFORATED INTERVALS: From 20								
From ft. to ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From30								
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other								
Grout Intervals: From .15 ft. to .3 ft., From								
What is the nearest source of possible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Sepage nit Feedward Fertilizer storage Oil well/gas well lift station								
wachtight sower mics Seepage pit Tecayard Technical storage On white gas well								
		LITHOLOG		ROM			GGING INTERVALS	
FROM	TO		ic too	ROM	10 LITHO. LA	JG (cont.) or PLU	GGING INTERVALS	
0	2	Top soil						
2	6	Brown clay						
6	30	Med. sand & gravel				· · ·		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .101310 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No134 This Water Well Record was completed on (mo/day/year) .10-21-10								
under the business name of .Rosencrantz-Bemis Ent. by (signature) Junior Dadata.								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy								