		LL RECORD	FORM W	/ C-3	$\overline{}$		r Kesources App. No			
1 LOCATION OF WATER WELL:			Fraction			ion Number		Range Number		
County: Reno		NW 1/4 NE 1/4 NE 1/4 NW 1/4			15		R 7 □E 🗹 W			
Street/Rural Address of Well Location; if unknown, distance & direction						Global Positioning System (GPS) information:				
		town or intersection: If at			Latit	ude:38,143	89	(in decimal degrees)		
							Longitude: 098.07919 (in decimal degrees)			
						Elevation: 1564				
						Datum: WGS 84, NAD 83, NAD 27				
2 WATER WELL OWNER: Smoky Hill LLC						Collection Method:				
RR#, Street Address, Box #: 645 E. Crawford Street						☐ GPS unit (Make/Model: Garmin csx				
at a grad a t						☐ Digital Map/Photo, Topographic Map, ☐ Land Survey				
City, State, ZIP Code : Salina, Kansas 67401						Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m				
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 35										
SEC	SECTION BOX: Depth(s) Groundwater Encountered (1)									
Pump test data: Well water wasft. after hours pumping										
N	w N		EST. YIELDgpm. Well water wasft. after hours pumpinggpm							
w	. .	E Bore Hole Diam	Bore Hole Diameter 28in. to .35ft., andin. toft.							
 		├── │ WELL WATER	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
Domestic D Feedlet D Oil field water supply Dewatering Dother (Specify below)								Other (Specify below)		
SW SE										
		Was a chemical/	bacteriological sample s							
	S						100 110			
S If yes, mo/day/yr sample was submitted										
·		. Water wen dish								
5 TYPE OF CASING USED: Steel V PVC Other										
CASING JOINTS: ☑ Glued ☐ Clamped ☐ Welded ☐ Threaded										
Casing diameter .16										
Casing height above land surface. 12 in., Weight SCH.40 lbs./ft., Wall thickness or gauge No500										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
Steel Stainless Steel PVC Other (Specify)										
Brass Galvanized Steel None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)										
□ Louvered shutter □ Key punched □ Wire wrapped ☑ Saw cut □ Other (specify)										
SCREEN-PERFORATED INTERVALS: From										
From ft. to ft., From ft. to ft.										
GRAVEL PACK INTERVALS: From										
From ft. to ft., From ft. to ft.										
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite										
Grout Intervals: From										
What is the nearest source of possible contamination:										
Septic tank										
Sewer lines										
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well										
Direction from well										
FROM	TO	LITHOLOG		FROM	TO TO			GGING INTERVALS		
			IC LOG	INON	10	LITTO. LC	C (COIII.) OI FLU	GOING INTERVALS		
0	2	Top soil								
2	6	Tan clay-silty								
6	20	Med. to coarse sand &	gravel							
20	35	Med. sand & gravel								

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged										
under my jurisdiction and was completed on (mo/day/year) .10-9-10 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No134 This Water Well Record was completed on (mo/day/year) .1015-10										
under the business name of Rosencrantz-Bemis Ent. by (signature)										
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies										
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.										
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.										
KSA 82a-1212 Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy										
					-	****				

20100288