

1 LOCATION OF WATER WELL: County: <u>Renov</u>	Fraction <u>NW 1/4 NW 1/4 SW 1/4</u>	Section Number <u>6</u>	Township Number <u>T 22 S</u>	Range Number <u>R 8 E</u>
---	--------------------------------------	-------------------------	-------------------------------	---------------------------

Distance and direction from nearest town or city street address of well if located within city?
From Sterling, KS: 3 miles South + 3 miles West

2 WATER WELL OWNER: <u>Jeff Probert</u> RR#, St. Address, Box # : <u>10002 North Sterling Rd.</u> City, State, ZIP Code : <u>Sterling, KS 67579</u>	Board of Agriculture, Division of Water Resources Application Number: <u>46.066</u>
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N - - NW - - - NE - - W - - - - - E - - SW - - - SE - - S	4 DEPTH OF COMPLETED WELL <u>65</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1 <u>12</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>12</u> ft. below land surface measured on mo/day/yr <u>5-19-05</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>200</u> gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ☒ Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No
--	--

5 TYPE OF BLANK CASING USED: 1 Steel ☒ PVC Blank casing diameter <u>16</u> in. to <u>40</u> in. Dia <u>60-65</u> in. to ft. Dia in. to ft. Casing height above land surface <u>36</u> in., weight <u>16</u> lbs./ft. Wall thickness or gauge No. <u>1/2"</u>	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued ☒ Clamped Welded Threaded	Blank casing diameter in. to ft. Dia in. to ft. Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.
---	---	---

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 8 RMP (SR) 9 ABS 11 Other (Specify) 12 None used (open hole)	SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)	SCREEN-PERFORATED INTERVALS: From <u>40</u> ft. to <u>60</u> ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>65</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.
--	--	--

6 GROUT MATERIAL: 1 Neat cement Grout Intervals: From <u>3</u> ft. to <u>28</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet? <u>Open Field</u>	7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-19-05</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>238</u> This Water Well Record was completed on (mo/day/yr) <u>5-25-05</u> under the business name of <u>Weninger Forstgater</u> by (signature) <u>Chris Weninger</u>
---	--

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	Topsoil			
6	10	Fine Sand			
10	58	Medium Sand to Small Gravel			
58	65	Grey Clay			
#3 SE Well					