

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Harvey	NE 1/4 NW 1/4 NE 1/4	24	T 23 S	R 1 E

Distance and direction from nearest town or city street address of well if located within city?

101 S. Evans Ave., Newton, Kansas

2 WATER WELL OWNER:	RR#, St. Address, Box	City of Newton Attn: Richard Oller	Board of Agriculture, Division of Water Resources
City, State, ZIP Code	City Hall, 125 E 7th, Newton, Kansas 67114	Application Number:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ELEVATION:
	25 ft.	
	Depth(s) Groundwater Encountered 1. 19.3 ft. 2. ft. 3. ft.	
	WELL'S STATIC WATER LEVEL 16.08 ft. below land surface measured on mo/day/yr 6/7/95	
	Pump test data: Well water was ft. after hours pumping gpm	
	Est. Yield gpm: Well water was ft. after hours pumping gpm	
	Bore Hole Diameter 8.625 in. to 25 ft., and in. to ft.	
	WELL WATER TO BE USED AS:	
	5 Public water supply 8 Air conditioning 11 Injection well	
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well MW-6	
	Was a chemical/bacteriological sample submitted to Department? Yes No X	
	Water Well Disinfected? Yes No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded X
2 PVC 4 ABS	7 Fiberglass		Threaded
Blank casing diameter 2 in. to 15 ft. Dia			
Casing height above land surface 0 in. weight SCH 40 PVC			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot 3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter 4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:	From 15 ft. to 25 ft.		
SAND GRAVEL PACK INTERVALS:	From 14 ft. to 25 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 12 ft. From 3 ft. to 12 ft. From 14 ft. to 14 ft.				
What is the nearest source of possible contamination:	1 Septic tank 4 Lateral lines 7 Pit privy	10 Livestock pens 14 Abandoned water well		
2 Sewer lines 5 Cess pool 8 Sewage lagoon	11 Fuel storage 15 Oil well/Gas well			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard	12 Fertilizer storage 16 Other (specify below)			
Direction from well?		How many feet?	Contaminated site	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
GL	1.00	Soil, silty clay			Flush Mount Wai
1.00	5.00	Silty clay (CL) redbrown, stiff			Don Taylor
5.00	18.00	Silty clay (CH) brown, stiff			6-6-95
18.00	25.00	Silty clay (CL) tan brown, soft			
25.00	TD	End of borehole			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/7/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 6/8/95 under the business name of Associated Environmental, Inc. by (signature) D Johnson for Dan Duncan
