1 LOCATION OF WATER WELL:			FRACTIO	N		CL WCII KC	aviu 10	AME IV IV C-	Section Number	Township Number	Range Number
Harvey		NW	1/4	NW	1/4	NW	1/4	31	<sub>τ</sub> 23 s	R 1W EW	
Distance and direction frem nearest town or city street address of well if located within city?											
1 m. E. of SE edge of Halstead, 1m. N., 1/8 E., south side Newton, KS.											
	ER WELL O										
FR <sub>3</sub> ,	T. ADRESS,	# <b>-</b>								Board of Agriculture,	Divivsion of Water Resource
	STATE, ZIP	code: Newton	, Kar	ısas					67114	Application Num	oer:
3 300 cm	I WELL'S L	I ROV:	DEPTH O					88		EVATION:	
N Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.											
				TIC W. mp test							11/03/1995
1	· · · · • • • · · · · · · · · · · · · ·	NE	Yield	mp test			ell wate: 'ell wate		ft. ft.	after hours pu	
₩ w			e Hole Diar	meter	gpm: 12	in.		88	ft.	after hours pu and in	
2 W		1 1 1	LL WATE						er supply		Injection well
	sw	1 1 1	1 Domesti		3 Feed				ater supply		Other (Specify below)
	SW	, y	2 Irrigatio	n	4 Indu	strial	7 La	wn and	garden only	10 Monitoring well	
ļ			s a chemica	al/bacte	riologica	d sample	e submit	tte <b>d</b> to D	epartment? Yes	No X ; If yes,	mo/day/yr sample was
S submitted Water Well Disinfected? Yes X No											
		SING USED:				ought ir			8 Concrete tile		Glued <b>X</b> Clamped
1 Stee		3 RMP (SR)		6 Asbestos-Cement 7 Fiberglass					Other (Specify	below)	Welded
2 PVC		4 ABS			7 Fibe	rglass		S	DR-26		Threaded
	sing Diam	_	to 68	_	ft.,	Dia		in		ft., Dia in.	to ft.
		e land surface 12 N OR PERFORATIO	N MATER	in., IAL:		weight	2.3		lbs. / ft. 7 PVC	Wall thickness or gauge No. 10 Asbestos-cer	.214
1 Stee		3 Stainless Steel			5 Fiber	glass			8 RMP (SR)	11 other (speci	fv)
2 Bras	*	4 Galvanized steel			6 Conci	rete tile			9 ABS	12 None used (	• *
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)											
	ious slot	3 Mill slot					Vire wra			9 Drilled holes	
2 harriered shutter 4 Key punched 7 Torch cut 10 Other (specify)											
SCREE	N-PERFO	RATION INTERVALS	: fro	m 68	ł		ft. to		ft., Fro	m ft. to	ft.
			fro		ft. to		•	ft., Fro			
GRAVEL PACK INTERVALS:			S: from	rom 24 ft. to 8		88	ft., Fro				
from					ft. to				ft., From ft. to		) ft.
	UT MATI			2 (	Cement gi				entonite	4 Other	
Grout Intervals: From 4 ft. to What is the nearest source of possible contar			to 24		ft.	From		ft.	to 10 Livest	ft. From tock pens 14	ft. to ft.
1 Septic tank 4 Lateral lin				7	7 Pit privy			11 Fuel s	*******	Abandon water well	
2 Sewer lines 5 Cess poo				8 Sewage lagoon					5 Oil well/Gas well 6 Other (specify below)		
	rtight sewe	-				Feedyar				ticide storage	odici (opecity below)
	n from wel					•				How many feet? 25	
FROM	TO	LIT	HOLOGIC	LOG			=	FROM	TO	PLUGGING INT	ERVALS
0 2	2	topsoil									
	20	clay								WINDLE STREET	
20	30	fine sand									
30	60	clay						**********			
60	88	medium to	coars	e s	and						
<b></b>	l										
l · ·										A CANADA AND A CAN	
										1994	
			***								A STATE OF THE PARTY OF THE PAR
											1 T MANUAL AND A STATE OF THE S
microsphera igni ten									1		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and											
was completed on (mo/day/year)											
Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 11/07/95											
Under the business name of Harp Well & Pump Service, Inc by (signature)											
İ										yane i	Frederick