

1 LOCATION OF WATER WELL: County: HAVEY		WATER WELL RECORD Fraction NE 1/4 NE 1/4 NE 1/4		Section Number 35		Township Number T 23 S		Range Number R 1 E/W																																																							
Distance and direction from nearest town or city street address of well if located within city? 3318 SW 24th RD. NEWTON, KS																																																															
2 WATER WELL OWNER: HARVEY CO RR#, St. Address, Box #: HARVEY COUNTY COURTHOUSE City, State, ZIP Code: P.O. BOX 687 NEWTON KS 67114 Board of Agriculture, Division of Water Resources Application Number:																																																															
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 1 Mile N W E S NW NE SW SE			4 DEPTH OF COMPLETED WELL: 26' ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 1/4 in. to 26' ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No																																																												
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped X 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 16' ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 36 in., weight sched 40 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: X 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot X 3 Mill slot 0.10 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 26 ft. to 16 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 26 ft. to 13 ft., From ft. to ft. From ft. to ft., From ft. to ft.																																																															
6 GROUT MATERIAL: 1 Neat cement + 5" X 2 Cement grout 13 3 Bentonite 11 4 Other Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? N.EAST 13 Insecticide storage LANDFILL How many feet? 1650'																																																															
<table border="1"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0</td><td>2.5</td><td>DRK BRN SILTY CLAY</td><td></td><td></td><td></td></tr><tr><td>2.5</td><td>5</td><td>BRN STIFF PLASTIC SILTY SANDY CLAY</td><td></td><td></td><td></td></tr><tr><td>5</td><td>11.5</td><td>FINE TO COARSE SANDY SILTY CLAY SOME CALICHE</td><td></td><td></td><td></td></tr><tr><td>11.5</td><td>15</td><td>VERY COARSE GRAINED SILTY SAND</td><td></td><td></td><td></td></tr><tr><td>15</td><td>18</td><td>BRN TO LIGHT GRAY SILTY CLAY</td><td></td><td></td><td></td></tr><tr><td>18</td><td>22</td><td>GRAY SOFT CLAYEY SILT</td><td></td><td></td><td></td></tr><tr><td>22</td><td>25.5</td><td>VERY COARSE GRAINED SILTY SAND</td><td></td><td></td><td></td></tr><tr><td>25.5</td><td>26</td><td>HARD DRY WELLINGTON SHALE</td><td></td><td></td><td></td></tr></tbody></table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	2.5	DRK BRN SILTY CLAY				2.5	5	BRN STIFF PLASTIC SILTY SANDY CLAY				5	11.5	FINE TO COARSE SANDY SILTY CLAY SOME CALICHE				11.5	15	VERY COARSE GRAINED SILTY SAND				15	18	BRN TO LIGHT GRAY SILTY CLAY				18	22	GRAY SOFT CLAYEY SILT				22	25.5	VERY COARSE GRAINED SILTY SAND				25.5	26	HARD DRY WELLINGTON SHALE			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																										
0	2.5	DRK BRN SILTY CLAY																																																													
2.5	5	BRN STIFF PLASTIC SILTY SANDY CLAY																																																													
5	11.5	FINE TO COARSE SANDY SILTY CLAY SOME CALICHE																																																													
11.5	15	VERY COARSE GRAINED SILTY SAND																																																													
15	18	BRN TO LIGHT GRAY SILTY CLAY																																																													
18	22	GRAY SOFT CLAYEY SILT																																																													
22	25.5	VERY COARSE GRAINED SILTY SAND																																																													
25.5	26	HARD DRY WELLINGTON SHALE																																																													
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (X) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-11-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 9-27-96 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature) <i>[Signature]</i>																																																															
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																															