


1 LOCATION OF WATER WELL: County: HARVEY		Fraction 1/4 SW 1/4 SW 1/4	Section Number 25	Township Number T 23 S	Range Number R 1 E <b>(W)</b>
Distance and direction from nearest town or city street address of well if located within city? 3318 S.W. 24th rd. NEWTON KS.					
2 WATER WELL OWNER: HARVEY CO. RR#, St. Address, Box # : HARVEY COUNTY COURTHOUSE City, State, ZIP Code : NEWTON, KS P.O. BOX 687 67114 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"></div>		4 DEPTH OF COMPLETED WELL: 13 ft. ELEVATION: Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 1/2 in. to 13 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only X10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped X 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded. Blank casing diameter 2 in. to 3 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 36 in. weight sched 40 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot X 3 Mill slot 6,10 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 13 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 13 ft. to 2.5 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement X 2 Cement grout X 3 Bentonite 4 Other Grout Intervals: From 1 ft. to +5" ft. From 2.5 ft. to 1 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? east How many feet? 1000'					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	5	FIRM TO SOFT SANDY CLAY SILT MOIST			
5	7	BRN SILTY SAND saturated			
7	10	BRN STIFF SILTY CLAY			
10	11.5	BRN STIFF PLASTIC SILTY CLAY			
11.5	12.5	BRN COARSE TO FINE GRAINED SILTY CLAY SAND CALICHE AT 13'			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X4 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-12-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 9-27-96 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature)					