CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

Location listed as:	County: Harvey Location changed to:
Section-Township-Range: 24-235-1F	24-235-/W
Fraction (1/4 1/4 1/4): SW SE NW	NW NW SW
Other changes: Initial statements:	
Changed to:	
Comments:	
verification method: <u>Well address</u> , <u>city</u> n Newton & Zimmerdale 1:24,00	nap on internet, and 00 topo. maps. initials: DEL date: 4/11/2005

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

			ER WELL RECORD	Form WWC-5	KSA 82a	· · · · · · · · · · · · · · · · · · ·	
	.	TER WELL: Fraction	25 M	/// Sec	tion Number	Township Number	Range Number
County:		from nearest town or city street	$\frac{\sqrt{4}}{3}\frac{35}{5}\frac{\sqrt{4}}{4}\frac{N}{1}$	d within situ?	27	TOS	R / - 12 (E)W
DISTANCE	and direction			-			
NA TE	D WELL OV		do court				
_	R WELL OV					Doord of Agricultura	Division of Water Becourses
O: O: .	Address, Bo	37	. (0331			A	, Division of Water Resources
City, State	e, ZIP Code	: Newton, Kansa OCATION WITH 4 DEPTH OF	8 0/114	67		Application Number:	
AN "X"	'IN SECTIO	N BOX:	COMPLETED WELL	رسي ب	ft. ELEVA	TION: 00.97.5	
_ r		Depth(s) Groun	idwater Encountered 1.	٠	π. 2	π.	3
Ī 1	-	WELL'S STATI	C WATER LEVELF.C	7 ft. b	elow land sur	face measured on mo/day/y	"
	NW					-	oumping gpm
1	ي ا						pumping gpm
≞ w ŀ	<u> </u>						in. to
_	-	1 i)		5 Public wate		•	1 Injection well
1	SW	SE 1 Domestic				9 Dewatering 12	
1 1	1	2 Irrigation			-	10 Monitoring well	
Į į			l/bacteriological sample s	submitted to De			es, mo/day/yr sample was sub-
-		ş mitted				ter Well Disinfected? Yes	
_		CASING USED:	5 Wrought iron	8 Concre			ed . 🗶 Clamped
1 S		3 RMP (SR)	6 Asbestos-Cement		(specify below	•	Ided
X 2 P	VC	4 ABS	7 Fiberglass			Thr	eaded
Blank cas	sing diameter		ft., Dia	in. to		ft., Dia	in. to ft.
-	_	and surface	in., weight				
		PERFORATION MATERIAL:		B PV		10 Asbestos-cen	
1 S		3 Stainless steel	5 Fiberglass		P (SR)		y)
	rass	4 Galvanized steel	6 Concrete tile	9 AB	S	12 None used (d	·
		RATION OPENINGS ARE:		ed wrapped		Saw cut	11 None (open hole)
	ontinuous sk			wrapped		9 Drilled holes	
	ouvered shu	ter 4 Key punched	47 Torch	cut 2	<u>.</u>	10 Other (specify)	
SCREEN	-PERFORAT						toft.
		From	ft. to	2.5	ft., Fror	n	toft.
	GRAVEL PA			6.3			
_		From	ft. to		ft., Fror		to ft.
	T MATERIA		2 Cement grout	(3)Bento			
		m. \mathcal{J} ft. to \mathcal{I} .3	ft., From	ft.			
_		ource of possible contamination:					Abandoned water well
	eptic tank	4 Lateral lines	7 Pit privy			storage 15	
	ewer lines	5 Cess pool	8 Sewage lago	oon		•	Other (specify below)
	-	ver lines 6 Seepage pit	9 Feedyard			ticide storage	
	from well?	W535		1	How mar	ny feet?	INTERVALO
FROM	то	LITHOLOGIC	CLOG	FROM	то	PLUGGING	INTERVALS
	-	2					
0	15	CLAY					
	A ••						
15	10	FRANTE SAMO					
0	30	CANY	4.				
	1			_			
30	63	5HADE -BICK					
			10.124				
		TO THE COME.					
7 CONT	RACTOR'S	OR LANDOWNER'S CERTIFICA	TION: This water well wa	as (1) constru	cted, (2) reco	nstructed, or (3) plugged u	nder my jurisdiction and was
		/year) 4-30-9					
		's License No 362					10-15-90
	business na				by (signat		d und
		typewriter or ball point pen. PLEASE PRESS		ease fill in blanke			copies to Kansas Department
		nent, Bureau of Water Protection; Topeka, I					