

1 LOCATION OF WATER WELL: County: Harvey		Fraction NE 1/4 SW 1/4 NW 1/4	Section Number 24	Township Number T 23 S	Range Number R 1W EW
Distance and direction from nearest town or city street address of well if located within city? 215 MEADOWLARK LN					
2 WATER WELL OWNER: Jim Hampton RR#, St. Address, Box # : 215 Meadowlark Lane City, State, ZIP Code : Newton, Kansas 67114 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 63' ft. ELEVATION: FLAT			
		Depth(s) Groundwater Encountered 1. 55 ft. 2. . ft. 3. . ft.			
		WELL'S STATIC WATER LEVEL . ft. below land surface measured on mo/day/yr 7-7-88			
		Pump test data: Well water was 60 ft. after 1 hours pumping 10 gpm			
		Est. Yield 8 gpm; Well water was . ft. after . hours pumping . gpm			
		Bore Hole Diameter . in. to 63 ft., and . in. to . ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes . No ✓ ; If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
X PVC		4 ABS		6 Asbestos-Cement	
Blank casing diameter . 5" in. to 43 ft., Dia . in. to . ft., Dia . in. to . ft.		7 Fiberglass		8 Concrete tile	
Casing height above land surface . 24 in., weight 2.29 lbs./ft. Wall thickness or gauge No. 214		9 Other (specify below)		CASING JOINTS: Glued X Clamped .	
TYPE OF SCREEN OR PERFORATION MATERIAL:		X PVO		10 Asbestos-cement	
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		8 RMP (SR)	
SCREEN OR PERFORATION OPENINGS ARE:		6 Concrete tile		9 ABS	
1 Continuous slot		5 Gauzed wrapped		X 8 Saw cut	
3 Mill slot		6 Wire wrapped		11 None (open hole)	
2 Louvered shutter		7 Torch cut		9 Drilled holes	
4 Key punched		10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From . 43 ft. to 63 ft., From . ft. to . ft.					
GRAVEL PACK INTERVALS: From . 10 ft. to 63 ft., From . ft. to . ft.					
6 GROUT MATERIAL: X Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From . 0 ft. to 10 ft., From . ft. to . ft., From . ft. to . ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
Direction from well? SOUTH		How many feet? 140			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	CLAY			
20	28	CLAY - FINE SAND			
28	36	HARD CLAY			
36	40	SHALE - BLUE			
40	60	SOFT SHALE			
60	63	GYP ROCK			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-7-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 362 This Water Well Record was completed on (mo/day/yr) 10-26-88 under the business name of Martin Supply by (signature) Bruce Schmidt					